DS 250[™]

		SPECIFICATIONS	DS 250
	ENGINE	Туре	249.4cc, 4-stroke, single, liquid-cooled, 4-valve SOHC
		Bore & Stroke	71 x 63 mm
		Torque	20 Nm @ 5,500 RPM
		Fuel Delivery	Keihin [‡] PTG 23
		Starting System	Electric
		Transmission	Automatic CVT, sub-transmission with forward, neutral & reverse
		Drive Train	Chain driven/solid axle
DS 250		Frame	DS 250
		Front Suspension Type	Double A-arm, 5-position adjustable pre-load
	<u>s</u>	Travel	5.5 in (140 mm)
		Rear Suspension Type	Swingarm, 5-position adjustable pre-load
		Travel	6.7 in (170 mm)
100	S	Front Brake	2 hydraulic discs
	CHAS	Rear Brake	1 hydraulic disc
Name and Address of the Owner, where the Owner, which is the Own	Ö	Tires/Front	22 x 7 x 10 in
			559 x 178 x 254 mm
		Tires/Rear	20 x 11 x 9 in
			508 x 279 x 229 mm
		Wheels	Steel, sport
		L x W x H (in)	72 x 40.5 x 43.5 in
	S	L x W x H (mm)	1,830 x 1,030 x 1,105 mm
	DIMENSIO	Wheelbase	47 in (1,187 mm)
		Seat Height	31.5 in (800 mm)
	M	Dry Weight	429 lbs (195 kg)
E CONTRACTOR OF THE PARTY OF TH	0	Ground Clearance	10.2 in (260 mm) center of ATV
		Fuel Capacity	3.3 US gal (12.5 L)
	ES	Instrumentation	Neutral light, reverse light and oil/temperature light
	EATURE	Lighting	2 headlamps (35W) with tail light/brake light
	AT	DC Outlet	Yes
And in case of the last of the	H	Standard Color	Yellow

©2007 Bombardier Recreational Products Inc (BRP). All rights reserved. The and the BRP logo are registered trademarks of Bombardier Recreational Products Inc, or its affiliates. ‡All other trademarks are the property of their respective owners. Products are distributed in the USA by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly, BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or in US. 2nd the ATV Safety Institute at 18009887-2887 in Canada, call the Canadian Safety Council at 16(3) 339-1535 et 927.4 TNVs can be Pazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol/drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving, Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater then 90c are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Can-Am^M Outlander MAX ATVs: These ATVs are recommended for drivers aged 16 and older, and passengers aged 12 and older only.



