DS 450[™]

		SPECIFICATIONS	DS 450
	ENGINE	Type Bore & Stroke Fuel Delivery Starting System Transmission Drive Train	449.3cc, single-cylinder, DOHC 4-valve, liquid-cooled 97 x 60.8 mm EFI with 46 mm Throttle Body, 16 bit CPU with 32 MHz clock speed Electric 5-speed manual Chain driven/solid axle
DS 450		Frame Front Suspension Type Travel Rear Suspension Type	ALTEC dual-pyramidal aluminum R-Type forged aluminum, Double A-arm/Kayaba† HPG aluminum piggyback with adjustment for compression, rebound and spring preload 9.5 in (241 mm) R-Type cast aluminum, swingarm/Kayaba HPG aluminum piggyback with
	CHASSIS	Travel Front Brake Rear Brake	adjustment for compression, rebound and spring preload 10.5 in (267 mm) Dual 182 mm wave type discs with inverted twin-piston calipers 198 mm wave type rotor with single piston caliper
		Tires/Front Tires/Rear Wheels	ITP Holeshot SR 21 x 7R-10 in 533 x 178R-254 mm ITP Holeshot SR 20 x 10R-9 in 508 x 254R-229 mm Aluminum, polished
DS 450 X	DIMENSIONS	L x W x H (in) L x W x H (mm) Wheelbase Seat Height Dry Weight Ground Clearance Fuel Capacity	72.4 x 46 x 41.9 in 1,839 x 1,168 x 1,064 mm 49.9 in (1,267 mm) 32.7 in (831 mm) 345 lbs (156.5 kg) 9 in (229 mm) under frame/5.2 in (132 mm) under rear axle 3 US gal (11.5 L)
	FEATURES	Instrumentation Lighting Standard Color	Low fuel, check engine, neutral Dual removable headlights Yellow
	PACKAGE	X Package Content Available X Color	Front Kayaba HPG piggyback shock with high & low speed compression adjustments, black rims with reinforcement rings, aluminum handlebar riser, aluminum taper-profile handlebar with square pad, aluminum front bumper (number plate ready), Nerf bars, chassis and swingarm aluminum skid plate, quick adjust clutch cable thumb screw, X package graphics, X package seat cover

©2007 Bombardier Recreational Products Inc (BRP). All rights reserved. TM® and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. ‡All other trademarks are the property of their respective owners. Products are distributed in the USA by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly, BRP highly recommends that all ATV drivers take a training course. For safety and training informations, see your cleaker or, in U.S. call the ATV Safety Institute at (1809) 887-2887. In Canada, call the Canadian Safety Ouncil at 1 (61) 3793-1535 ex 172. ATVs can be Pazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing, Always remember that riding and alcohol/drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving, Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Can-AmTM Outlander MAX ATVs: These ATVs are recommended for drivers aged 16 and older, and passengers aged 12 and older only.



