

# OUTLANDER™ 400 H.O.

		SPECIFICATIONS	OUTLANDER 400 H.O.	OUTLANDER MAX 400 H.O.
 <p>Outlander 400 H.O.</p>	ENGINE	Type Bore & Stroke Torque Fuel Delivery Starting System Transmission Drive Train	400cc, 4-stroke, single, liquid-cooled, 4-valve SOHC 91 x 61.5 mm 32 Nm @ 5,500 RPM Mikuni® BSR 33 Electric with auxiliary recoil CVT, sub-transmission with high, low, park, neutral & reverse Selectable 2w/4w shaft driven with Visco-Lok® front differential	400cc, 4-stroke, single, liquid-cooled, 4-valve SOHC 91 x 61.5 mm 32 Nm @ 5,500 RPM Mikuni BSR 33 Electric with auxiliary recoil CVT, sub-transmission with high, low, park, neutral & reverse Selectable 2w/4w shaft driven with Visco-Lok front differential
	CHASSIS	Frame Front Suspension Type Travel Rear Suspension Type Travel Front Brake Rear Brake Tires/Front Tires/Rear Wheels	SST MacPherson† 7 in (178 mm) TTI independent 8 in (203.2 mm) 2 inboards hydraulic discs 1 inboard hydraulic disc 25 x 8 x 12 in 635 x 203 x 305 mm 25 x 10/11(XT) x 12 in 635 x 254/279(XT) x 305 mm Steel	SST MacPherson 7 in (178 mm) TTI independent 8 in (203.2 mm) 2 inboards hydraulic discs 1 inboard hydraulic disc 25 x 8 x 12 in 635 x 203 x 305 mm 25 x 10/11(XT) x 12 in 635 x 254/279(XT) x 305 mm Steel
 <p>Outlander 400 H.O. XT</p>	DIMENSIONS	L x W x H (in) L x W x H (mm) Wheelbase Seat Height Dry Weight Ground Clearance Rack Capacity Towing Capacity Fuel Capacity	86 x 46 x 45 in 2,184 x 1,168 x 1,143 mm 49 in (1,244 mm) 35 in (877 mm) 615 lbs (279 kg) 9.3 in (236 mm) Front: 100 lbs (45 kg) Rear: 200 lbs (90 kg) 1,100 lbs (500 kg) 4.2 US gal (16 L)	94 x 46 x 45 in 2,387 x 1,168 x 1,143 mm 57 in (1,447 mm) 35 in (877 mm) 665 lbs (302 kg) 9.3 in (236 mm) Front: 100 lbs (45 kg) Rear: 200 lbs (90 kg) 1,100 lbs (500 kg) 4.2 US gal (16 L)
 <p>Outlander MAX 400 H.O.</p>	FEATURES	Instrumentation Storage Electrical Lighting DC Outlet Standard Colors	Digital gauge: Speedometer, odometer, trip and hourmeters, gear position, 4x4 indicator Rear storage 5.3 US gal (20 L) Prewired for winch 2 fender mounted headlamps (35W) with tail light/brake light Lighter type in console, standard connector in the back (15A) Yellow, Viper Red	Digital gauge: Speedometer, odometer, trip and hourmeters, gear position, 4x4 indicator Rear storage 5.3 US gal (20 L) CRS (Convertible Rack System) Prewired for winch 2 fender mounted headlamps (35W) with tail light/brake light Lighter type in console, standard connector in the back (15A) Viper Red
 <p>Outlander MAX 400 H.O. XT</p>	PACKAGE	XT Package Content Available XT Colors	BRP XL3000 winch, roller fairlead, wired remote control, cast aluminum rims, aggressive tread Carlisle® ACT radial tires, heavy-duty front & rear bumpers, handlebar wind deflector Yellow, Viper Red, Laurentian Green	BRP XL3000 winch, roller fairlead, wired remote control, cast aluminum rims, aggressive tread Carlisle ACT radial tires, heavy-duty front & rear bumpers, handlebar wind deflector Yellow, Viper Red, Laurentian Green

©2007 Bombardier Recreational Products Inc. (BRP). All rights reserved.™ and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. Visco-Lok is a trademark of GKN ViscoDrive GmbH. †All other trademarks are the property of their respective owners. Products are distributed in the USA by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S. call the ATV Safety Institute at 1(800) 887-2887. In Canada, call the Canadian Safety Council at 1(613) 739-1535 ext. 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol/drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Can-Am™ Outlander MAX ATVs: These ATVs are recommended for drivers aged 16 and older, and passengers aged 12 and older only.

**can-am**  
THE ULTIMATE RIDE™

