


# OUTLANDER™ 500 H.O. EFI

		SPECIFICATIONS	OUTLANDER 500 H.O. EFI 4x4	OUTLANDER MAX 500 H.O. EFI 4x4
 <p><b>Outlander 500 H.O. EFI 4x4</b></p>	ENGINE	Type	499.6cc, 4-stroke, V-twin, liquid-cooled, 8-valve SOHC	499.6cc, 4-stroke, V-twin, liquid-cooled, 8-valve SOHC
		Bore & Stroke	82 x 47 mm	82 x 47 mm
 <p><b>Outlander 500 H.O. EFI XT 4x4</b></p>	CHASSIS	Torque	42 Nm @ 6,000 RPM	42 Nm @ 6,000 RPM
		Fuel Delivery	46 mm Throttle Body, 2 Siemens <sup>†</sup> VDO injectors	46 mm Throttle Body, 2 Siemens VDO injectors
 <p><b>Outlander MAX 500 H.O. EFI 4x4</b></p>	DIMENSIONS	Starting System	Electric	Electric
		Transmission	CVT, sub-transmission with high, low, park, neutral & reverse	CVT, sub-transmission with high, low, park, neutral & reverse
 <p><b>Outlander MAX 500 H.O. EFI XT 4x4</b></p>	FEATURES	Drive Train	Selectable 2w/4w shaft driven with Visco-Lok <sup>†</sup> front differential	Selectable 2w/4w shaft driven with Visco-Lok front differential
		Frame	SST	SST
	PACKAGE	Front Suspension Type	MacPherson <sup>†</sup>	MacPherson
		Travel	7 in (178 mm)	7 in (178 mm)
		Rear Suspension Type	TTL independent	TTL independent
		Travel	9 in (228.6 mm)	9 in (228.6 mm)
		Front Brake	2 inboard hydraulic discs	2 inboard hydraulic discs
		Rear Brake	1 inboard hydraulic disc	1 inboard hydraulic disc
		Tires/Front	25 x 8 x 12 in 635 x 203 x 305 mm	25 x 8 x 12 in 635 x 203 x 305 mm
		Tires/Rear	25 x 10/11(XT) x 12 in 635 x 254/279(XT) x 305 mm	25 x 10/11(XT) x 12 in 635 x 254/279(XT) x 305 mm
		Wheels	Steel	Steel
		L x W x H (in)	86 x 46 x 45 in	94 x 46 x 45 in
		L x W x H (mm)	2,184 x 1,168 x 1,143 mm	2,387 x 1,168 x 1,143 mm
		Wheelbase	51 in (1,295 mm)	59 in (1,499 mm)
		Seat Height	34.5 in (877 mm)	34.5 in (877 mm)
		Dry Weight	642 lbs (291 kg)	685 lbs (311 kg)
		Ground Clearance	11 in (279 mm)	11 in (279 mm)
		Rack Capacity	Front: 100 lbs (45 kg) Rear: 200 lbs (90 kg)	Front: 100 lbs (45 kg) Rear: 200 lbs (90 kg)
		Towing Capacity	1,300 lbs (590 kg)	1,300 lbs (590 kg)
		Fuel Capacity	5.3 US gal (20 L)	5.3 US gal (20 L)
		Instrumentation	Multi-function digital LCD gauge: Speedometer, tachometer, odometer, trip & hour meter, fuel, gear position & 4x4 indicator, diagnostics, auto shut off after 15 minutes	Multi-function digital LCD gauge: Speedometer, tachometer, odometer, trip & hour meter, fuel, gear position & 4x4 indicator, diagnostics, auto shut off after 15 minutes
		Anti-Theft	D.E.S.S. (Digital Encoded Security System)	D.E.S.S. (Digital Encoded Security System)
		Storage	Rear storage 5.3 US gal (20 L)	Rear storage 5.3 US gal (20 L) CRS (Convertible Rack System)
		Electrical	Prewired for winch	Prewired for winch
		Lighting	2 fender mounted headlamps (35W) with tail light/brake light	2 fender mounted headlamps (35W) with tail light/brake light
		DC Outlet	Lighter type in console, standard connector in the back (15A)	Lighter type in console, standard connector in the back (15A)
		Standard Colors	Yellow, Viper Red	Viper Red
		XT Package Content Available	BRP XL3000 winch, roller fairlead, wired remote control, cast aluminum rims, aggressive tread Carlisle <sup>†</sup> ACT radial tires, heavy-duty front & rear bumpers, handlebar wind deflector	BRP XL3000 winch, roller fairlead, wired remote control, cast aluminum rims, aggressive tread Carlisle ACT radial tires, heavy-duty front & rear bumpers, handlebar wind deflector
		XT Colors	Yellow, Viper Red, Laurentian Green, Camo	Yellow, Viper Red, Laurentian Green, Camo

©2007 Bombardier Recreational Products Inc. (BRP). All rights reserved. <sup>™</sup> and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. <sup>†</sup>Visco-Lok is a trademark of GKN ViscoDrive GmbH. <sup>‡</sup>All other trademarks are the property of their respective owners. Products are distributed in the USA by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S. call the ATV Safety Institute at 1(800) 887-2887. In Canada, call the Canadian Safety Council at 1(613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol/drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Can-Am<sup>™</sup> Outlander MAX ATVs: These ATVs are recommended for drivers aged 16 and older, and passengers aged 12 and older only.

**can-am**  
THE ULTIMATE RIDE<sup>™</sup>

