# RENEGADE™ 500 H.O. EFI

Renegade
500 H.O. EFI 4x4

| | SPECIFICATIONS | RENEGADE 500 H.O. EFI 4x4 |
|---|---|---|
| ENGINE | Type | 499.6cc, 4-stroke, V-twin, liquid-cooled, 8-valve SOHC |
| | Bore & Stroke | 82 x 47 mm |
| | Torque | 42 Nm @ 6,000 RPM |
| | Fuel Delivery | 46 mm Throttle Body, 2 Siemens‡ VDO injectors |
| | Starting System | Electric |
| | Transmission | CVT, sub-transmission with high, low, park, neutral & reverse |
| | Drive Train | Selectable 2w/4w shaft driven with Visco-Lok† front differential |
| CHASSIS | Frame | SST |
| | Front Suspension Type | RS-Type Double A-arm, forged aluminum upper arm, Motion Control shocks |
| | Travel | 8.5 in (216 mm) |
| | Rear Suspension Type | RS-Type TTI independent, Motion Control shocks |
| | Travel | 9 in (229 mm) |
| | Front Brake | 2 hydraulic discs |
| | Rear Brake | 1 inboard hydraulic disc |
| | Tires/Front | ITP Holeshot ATRs<br>25 x 8 x 12 in<br>635 x 203 x 305 mm |
| | Tires/Rear | ITP Holeshot ATR<br>25 x 10 x 12 in<br>635 x 254 x 305 mm |
| | Wheels | Center cast aluminum |
| DIMENSIONS | L x W x H (in) | 86 x 46 x 45 in |
| | L x W x H (mm) | 2,184 x 1,168 x 1,143 mm |
| | Wheelbase | 51 in (1,295 mm) |
| | Seat Height | 34.5 in (877 mm) |
| | Dry Weight | 607 lbs (275 kg) |
| | Ground Clearance | 11 in (279 mm) |
| | Rack Capacity | Rear: 35 lbs (16 kg) |
| | Towing Capacity | 1,300 lbs (590 kg) |
| | Fuel Capacity | 5.3 US gal (20 L) |
| FEATURES | Instrumentation | Multi-function gauge:<br>Speedometer, tachometer, odometer, trip and hourmeters, fuel, gear position, 4x4 indicator, diagnostics, auto shut off |
| | Anti-Theft | D.E.S.S. (Digital Encoded Security System) |
| | Storage | Rear storage 1 US gal (3.7 L) |
| | Electrical | Prewired for winch |
| | Lighting | 4 fender mounted Projector Beam headlamps (60W)<br>with tail light/brake light |
| | DC Outlet | Lighter-type in console, standard connector in the back (15A) |
| | Standard Color | Yellow |

©2007 Bombardier Recreational Products Inc (BRP). All rights reserved. ™® and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. Products are distributed in the USA by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S. call the ATV Safety Institute at 1(800) 887-2887. In Canada, call the Canadian Safety Council at 1(613) 739-1535 ext 227. **ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol/drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain.** ATVs with engine sizes of greater then 90cc are recommended for use only by those age 16 and older. **Never carry passengers on any ATV not specifically designated for such use.** Can-Am™ Outlander MAX ATVs: These ATVs are recommended for drivers aged 16 and older, and passengers aged 12 and older only.

can-am™
THE ULTIMATE RIDE™

BRP

REVISED AUGUST 21, 2007