



DS 450 EXCLUSIVE PACKAGES

X mx PACKAGE ADDS:

- + 2" double A-arms with adjustable caster and camber give a 50-inch+ front stance
- Kashima-coated KYB HPG C40 aluminum piggyback front shocks with dual-speed compression, rebound and preload adjustments, and 10.7" (272 mm) of travel
- Kashima-coated KYB HPG C46 aluminum remote reservoir rear shock with dual-speed compression, rebound and preload adjustments, and 10.7" (272 mm) of travel
- 7" (179 mm) factory-set ride height (175-lb rider)
- 20 x 6-10 ITP QuadCross MX PRO front tires
- 18 x 10-8 ITP QuadCross MX PRO rear tires
- Black aluminum ITP 10 x 5 T-9 GP front wheels
- Black aluminum ITP 8 x 8 T-9 Trac-lock rear wheels
- X mx race graphics

X xc PACKAGE ADDS:

- R-type forged aluminum double A-arms with adjustable caster
- KYB HPG C36 aluminum piggyback front shocks with dual-speed compression, rebound and preload adjustments, and 9.5" (241 mm) of travel
- KYB HPG C40 aluminum piggyback rear shock with dual-speed compression, rebound and preload adjustments, and 10.5" (267 mm) of travel
- 7.5" (190 mm) factory-set ride height (175-lb rider)
- 21 x 7-10 ITP Holeshoot GNCC 6-ply front tires
- 20 x 10-9 ITP Holeshoot GNCC 6-ply rear tires
- Black aluminum ITP 10 x 5 T-9 Trac-lock front wheels
- Black aluminum ITP 9 x 8 T-9 Trac-lock rear wheels
- 3-mm full aluminum chassis skid plate
- 5-mm full aluminum swing arm skid plate
- Handlebar wind deflectors
- X xc race graphics

BOTH PACKAGES ALSO ADD:

- Tether engine-shut-off switch
- Adjustable-width hollow rear axle (from 46" [1.17 m] to 50" [1.27 m] by increments of 0.5" [12.7 mm] per spacer)
- Extra-strength extended 1" (25.4 mm) steering stem with anti-vibe mounts
- Aluminum nerf bars with removable heel guards and side extensions
- Aluminum 6061-T6 taper-profile handlebar with square pad
- Aluminum front bumper, number plate ready
- X package seat cover
- Color: Black ■

SPECIFICATIONS

ENGINE

Type	449.3cc, single-cylinder, liquid-cooled, DOHC 4-valve head with high-flow "Durchzugskraft" design, 38mm intake valve, 31 mm Nimonic – alloy
Bore & Stroke	97 x 60.8 mm
EFI System/Carburetor	46 mm Throttle Body, 16 bit/32 MHz CPU
Starting System	Electric
Transmission	5-speed manual/Heavy-duty clutch, 9 friction plates with DirectLink mechanism
Drive Train	520 O-ring high capacity chain, aluminum sprocket hub, aluminum sprocket, rigid axle

DIMENSIONS

L x W x H (in)	72.4 x 46 x 41.9 in
L x W x H (mm)	1,839 x 1,168 x 1,064 mm
Wheelbase	50 in (1,267 mm)
Seat Height	33 in (831 mm)
Ground Clearance	9 in under frame/5.2 in under rear axle
Dry Weight	345 lbs (156.5 kg)
Fuel Capacity	3 US gal (11.5L)



WARRANTY

Basic	6 months limited factory warranty
Extended	B.E.S.T. available from 12 to 36 months

CHASSIS

Frame	ALTEC dual-pyramidal aluminum
Front Suspension Type/Shocks	R-Type forged aluminum double A-arm, KYB HPG piggyback shocks with compression, rebound and preload adjustments
Front Suspension Travel	9.5 in (241 mm)
Rear Suspension Type/Shocks	R-Type cast aluminum swingarm, Chromoly hollow rear axle
Rear Suspension Travel	10.5 in (267 mm)
Front Brake	Dual 182 mm discs with inverted twin-piston calipers
Rear Brake	198 mm rotor with single piston caliper
Front Tires	ITP Holeshoot SR 21 x 7R-10 in 533 x 178R-254 mm
Rear Tires	ITP Holeshoot SR 20 x 10R-9 in 508 x 254R-229 mm
Wheels	Aluminum polished

FEATURES

Instrumentation	Low fuel, check engine, neutral
Lighting	Dual removable headlights (35W)
Colors Available	Yellow  Can-Am Red 



©2008 Bombardier Recreational Products Inc (BRP). All rights reserved.™ and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. Products are distributed in the USA by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S. call the ATV Safety Institute at 1(800) 887-2887. In Canada, call the Canadian Safety Council at 1(613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol/drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Can-Am™ Outlander MAX ATVs: These ATVs are recommended for drivers aged 16 and older, and passengers aged 12 and older only.

can-am
THE ULTIMATE RIDE™

