



DS 250®



SPECIFICATIONS

ENGINE

Type	249.4cc, single cylinder, liquid-cooled, SOHC, 4-valve
Bore & Stroke	71 x 63 mm
EFI System/Carburetor	Keihin™ PTG 23
Starting System	Electric
Transmission	Automatic CVT, sub-transmission with forward, neutral & reverse
Drive Train	Chain driven/solid axle

CHASSIS

Frame	DS 250
Front Suspension	Double A-arm
Type/Shocks	5-position adjustable preload
Front Suspension Travel	5.5 in (140 mm)
Rear Suspension	Swingarm
Type/Shocks	5-position adjustable preload
Rear Suspension Travel	6.7 in (170 mm)
Front Brake	2 hydraulic discs
Rear Brake	1 hydraulic disc
Tires/Front	22 x 7 x 10 in 559 x 178 x 254 mm
Tires/Rear	20 x 11 x 9 in 508 x 279 x 229 mm
Wheels	Steel

WARRANTY

Basic	6 months limited factory warranty
Extended	B.E.S.T. available from 12 to 36 months

DIMENSIONS

L x W x H (in)	72 x 40.5 x 43.5 in
L x W x H (mm)	1,830 x 1,030 x 1,105 mm
Wheelbase	47 in (1,187 mm)
Seat Height	31.5 in (800 mm)
Ground Clearance	10.2 in (260 mm) center of ATV
Dry Weight	429 lb (195 kg)
Fuel Capacity	3.3 US gal (12.5L)

FEATURES

Instrumentation	Neutral light, reverse light and oil/temperature light
Lighting	2 headlamps (35W) with tail light/brake light
DC Outlet	Yes
Color	Yellow 