



RENEGADE 500

SPECIFICATIONS

low, park, neutral & reverse. Standard engine braking Drive Train Selectable 2w/4w shaft driven		
SOHC, 8-valve (4-valve/cyl) Bore & Stroke 82 x 47 mm EFI System/ Carburetor 2 Siemens® VDO injectors Starting System Electric Transmission CVT, sub-transmission with high low, park, neutral & reverse. Standard engine braking Drive Train Selectable 2w/4w shaft driven	ENGINE	
EFI System/ Carburetor 2 Siemens® VDO injectors Starting System Electric Transmission CVT, sub-transmission with high low, park, neutral & reverse. Standard engine braking Drive Train Selectable 2w/4w shaft driven	Туре	, , ,
Carburetor 2 Siemens VDO injectors Starting System Electric Transmission CVT, sub-transmission with high low, park, neutral & reverse. Standard engine braking Drive Train Selectable 2w/4w shaft driven	Bore & Stroke	82 x 47 mm
Transmission CVT, sub-transmission with high low, park, neutral & reverse. Standard engine braking Drive Train Selectable 2w/4w shaft driven	,	3,
low, park, neutral & reverse. Standard engine braking Drive Train Selectable 2w/4w shaft driven	Starting System	Electric
	Transmission	
	Drive Train	Selectable 2w/4w shaft driven with Visco-Lok† front differential

DIMENSIONS	
L x W x H (in)	86 x 46 x 45 in
L x W x H (mm)	2,184 x 1,168 x 1,143 mm
Wheelbase	51 in (1,295 mm)
Seat Height	34.5 in (877 mm)
Ground Clearance	11 in (279 mm)
Dry Weight	614 lb (279 kg)
Towing Capacity	1,300 lb (590 kg)
Rack Capacity	35 lb (16 kg)
Storage	Rear: 1 US gal (3.7L)
Fuel Capacity	4.3 US gal (16.3L)



CH	assi	S
----	------	---

CUA2212	
Frame	SST
Front Suspension	RS-Type Double A-arm/
Type/Shocks	Motion Control shocks
Front Suspension	8.5 in (216 mm)
Travel	
Rear Suspension	RS-Type Torsional Trailing arm
Type/Shocks	Independent (TTI)/
	Motion Control shocks
Rear Suspension	9 in (229 mm)
Travel	
Front Brake	2 hydraulic discs
Rear Brake	1 inboard hydraulic disc
Tires/Front	ITP Holeshot [∞] ATR
	25 x 8 x 12 in
	635 x 203 x 305 mm
Tires/Rear	ITP Holeshot ATR
	25 x 10 x 12 in
	635 x 254 x 305 mm

Wheels Center-cast aluminum

FEATURES

FEATURES	
Instrumentation	Multi-function gauge: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock, auto shut off
Anti-theft System	D.E.S.S.™ (Digital Encoded Security System)
Electrical	Prewired for winch
Lighting	4 fender mounted projector beam headlamps (60W) with tail light/brake light
DC Outlet	Lighter type in console, standard connector in the back (15A)
Colors Available	Yellow White

WARRANTY

Basic	6 months limited factory warranty
Extended	B.E.S.T. available from
	12 to 36 months





