

STANDARD SPECIFICATIONS

ENGINE CHOICE	1000R	DIMENSIONS	
Туре	976 cc, V-twin, liquid-cooled, SOHC, 8-valve (4-valve / cyl)	L x W x H (in.)	148 x 64 x 78 in.
Bore & Stroke	91 x 75 mm	LxWxH(cm)	376 x 162.5 x 198 cm
Fuel System	iTC™ with EFI and 54 mm Throttle Body, 2 Siemens† VDO injectors	Wheelbase	113.8 in. (289.1 cm)
Starting System	Electric	Ground Clearance Rear Rack	12.5 in. (31.75 cm)
Transmission	CVT, sub-transmission with high, low, park, neutral & reverse. Standard engine braking		
Drive Train	Selectable 2WD / 4WD shaft driven with Visco-Lok [‡] auto-locking front differential	Capacity Cockpit Storage	quick-attach accessory system Glove box: 4.5 gal (17.2 L)
CHASSIS	VISCO-LOK AUTO-IOCKING HOUL UNITEICHTIAI	Cockpit Storage	Under driver seat: 3.5 gal (13.1 L) Center console: 0.3 gal (1.3 L)
	01. 1	Fuel Capacity	10 gal (37.8 L)
Frame	Steel		
Cage Type	2-in. (5.1 cm) diameter, high-strength steel, ROPS-approved	FEATURES	
Steering Wheel Adjustment	Adjustable tilt steering	Instrumentation	Multifunction gauge: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off
Front Suspension Type	Double A-arm		
Front Shocks Type	FOX [†] PODIUM [†] X Performance 2.0 HPG Piggyback shocks with compression and preload adjustments		
Front Suspension Travel	14 in. (35.6 cm)	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
Rear Suspension Type	Torsional Trailing A-arms independent rear suspension (TTA) with sway bar		
Rear Shocks Type	FOX PODIUM X Performance 2.0 HPG Piggyback shocks with compression	Electrical	Prewired for winch
Rear Suspension Travel	and preload adjustments 14 in. (35.6 cm)	Lighting	240-W from four 60-W projectors with tail lights / brake light
Front Brake	Dual 220 mm ventilated disc brakes with		
TIOIL DIAKC	hydraulic twin-piston (32 mm) calipers	WARRANTY	
Rear Brake	Dual 214 mm ventilated disc brakes with hydraulic single-piston (32 mm) caliper	Factory	6 months limited warranty
Tires / Front	Maxxis Bighorn 2.0 [†] 27 x 9 x 12 in. (68.6 x 22.9 x 30.5 cm)	Extended	B.E.S.T. available from 6 to 30 months
Tires / Rear	Maxxis Bighorn 2.0 27 x 11 x 12 in. (68.6 x 27.9 x 30.5 cm)		
Wheels	Cast-aluminum		

©2013 Bombardier Recreational Products Inc (BRP). All rights reserved. M, and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. ‡ Visco-Lok is a trademark of GKN Viscodrive GmbH. Tall other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include from a features, models or equipment without incurring obligation. Some models depicted may include great Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving, For your safety, wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Drive responsibly.

1,547 lb (702 kg)





DRY WEIGHT

STANDARD FEATURES

MAVERICK MAX

INDUSTRY-LEADING PERFORMANCE

- 101-hp Rotax® 1000R V-Twin engine with high-flow dynamics
- Intelligent Throttle Control (iTC)
- Continuously Variable Transmission (CVT) with Zylon†-reinforced belt
- Dual exhaust
- 10-gal (37.8 L) fuel tank

PRECISION-ENGINEERED HANDLING

- Mid-engine layout for mass centralization
- Double A-arm front suspension with 14 in. (35.6 cm) of travel
- Front and rear FOX PODIUM X Performance
- 2.0 HPG Piggyback shocks

 Torsional Trailing A-arms independent rear suspension (TTA) with 14 in. (35.6 cm) of travel

 Torsional Trailing A-arms independent rear suspension (TTA) with 14 in. (35.6 cm) of travel
- Visco-Lok auto-locking front differential
- 12.5 in. (31.75 cm) of ground clearance Front (220 mm) and rear (214 mm) dual ventilated disc brakes
- 27-in. Maxxis Bighorn 2.0 tires
- 12-in. center-less cast-aluminum wheels
- · High frame rigidity

RIDER-FOCUSED DESIGN

- High-strength, 150-lb (68 kg) multipurpose rear rack with LinQ quick-attach system
- 2-in. (5.1 cm) diameter, high-strength steel, ROPS-approved cage

 • Adjustable driver's seat and tilt steering
- · Passenger handhold and grab bar
- 8.3 gal (31.6 L) of cockpit storage
- Digitally Encoded Security System (D.E.S.S.) anti-theft system, with 2 different keys
- Multifunction digital gauge



COLOR AND ENGINE OPTION

Yellow - 1000R

PACKAGE OPTION

NEW MAVERICK MAX X° rs DPS

ADDED FEATURES

- Tri-Mode Dynamic Power Steering (DPS)
- Visco-Lok QE
- Front and rear FOX PODIUM X Performance RC2.5 HPG Piggyback shocks with dual speed compression, rebound and preload adjustments
- 12-in. aluminum beadlock wheels
- Analog / digital gauge
- Custom steering wheel with brushed-aluminum center part
- X-package seat trim and graphics

COLOR AND ENGINE OPTIONS

Yellow & Black 1000R NEW White, Black & Can-Am® Red 1000R

NEW Can-Am Red 1000R



MAVERICK MAX—GENUINE ACCESSORIES







Whether you need them for dune or trail riding, all the accessories are built and designed by BRP to specifically match your vehicle, without compromises, increase comfort and versatility — and give you that unmistakable Can-Am look.



