

10000

# **STANDARD SPECIFICATIONS**

ENGINE QUOIDE

**DRY WEIGHT** 

ENGINE CHOICE	1000R	DIMENSIONS	
Туре	976 cc, V-twin, liquid-cooled, SOHC, 8-valve (4-valve/cyl)	L x W x H (in.)	118.8 x 64 x 74.2 in.
Bore & Stroke	91 x 75 mm	LxWxH(mm)	3,017 x 1,626 x 1,885 mm
Fuel System	iTC $^{\sim}$ with EFI and 54 mm Throttle Body, 2 Siemens $^{\dagger}$ VDO injectors	Wheelbase	84.3 in. (2,141 mm)
Starting System	Electric	Ground	13 in. (330 mm)
Transmission	CVT, sub-transmission with high, low, park, neutral & reverse. Standard engine braking	Clearance Rear Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach system
Drive Train	Selectable 2WD / 4WD shaft driven with		
	Visco-Lok® auto-locking front differential	Cockpit Storage	Glove box: 4.5 gal (17.2 L) Under driver seat: 3.5 gal (13.1 L) Center console: 0.3 gal (1.3 L)
OHACCIC			
CHASSIS		Fuel Capacity	10 gal (37.8 L)
Frame	Steel		
Cage Type	2-in. (51 mm) diameter, high-strength steel, ROPS-approved	<b>FEATURES</b>	
Steering Wheel Adjustment	Adjustable tilt steering	Instrumentation	Multifunction gauge: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, seat belt and 4x4 indicator, diagnostics, clock, auto shut off
Front Suspension Type	Double A-arm		
Front Shocks Type	FOX <sup>†</sup> PODIUM <sup>†</sup> X Performance 2.0 HPG piggyback shocks with compression and preload adjustments		
Front Suspension Travel	14 in. (356 mm)	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
Rear Suspension Type	Torsional Trailing A-arms (TTA) independent rear suspension with sway bar		
Rear Shocks Type	FOX PODIUM X Performance 2.0 HPG piggyback shocks with compression	Electrical Lighting	Prewired for winch
Dana Cuananaian Tuanal	and preload adjustments		4 60-W projectors with tail lights / brake light
Rear Suspension Travel	14 in. (356 mm)		tan ngnts / brake ngnt
Front Brake	Dual 214 mm ventilated disc brakes with hydraulic twin-piston (27 mm) calipers	WARRANTY	
Rear Brake	Dual 214 mm ventilated disc brakes with hydraulic single-piston (32 mm) caliper	Factory	6 months limited warranty
Tires / Front	Maxxis Bighorn 2.0 <sup>†</sup> 27 x 9 x 12 in. (686 x 229 x 305 mm)	Extended	B.E.S.T. available from 6 to 30 months
Tires / Rear	Maxxis Bighorn 2.0 27 x 11 x 12 in. (686 x 279 x 305 mm)		
Wheels	Cast-aluminum		

©2012 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. Tisco-Lok is a trademark of GRN Viscodrive GmbH. † All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include inotal equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old, Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Drive responsibly.

1,297 lb (588 kg)



DIMENSIONS



# STANDARD FEATURES

# **MAVERICK**

## **INDUSTRY-LEADING PERFORMANCE:**

- 101-hp Rotax® 1000R V-Twin engine with high-flow dynamics
- Intelligent Throttle Control (iTC)
- Continuously Variable Transmission (CVT) with Zylon<sup>†</sup>-reinforced belt
- Dual exhaust
- 10-gal (37.8 L) fuel tank

### PRECISION-ENGINEERED HANDLING:

- Mid-engine layout for mass centralization
- Double A-arm front suspension with 14 in. of travel
   Front and rear FOX PODIUM X Performance
- 2.0 HPG piggyback shocks
- Torsional Trailing A-arms (TTA) independent rear suspension with 14 in. of travel

- Visco-Lok auto-locking front differential
  13 in. (33 cm) of ground clearance
  Front and rear dual 214-mm ventilated disc brakes
- 27-in. (68.6 cm) Maxxis Bighorn 2.0 tires
- 12-in. center-less cast-aluminum wheels
- · High frame rigidity

# RIDER-FOCUSED DESIGN:

- High-strength, 200-lb (91 kg) multipurpose rear rack with LinQ quick-attach system

  • 2-in. (51 mm) diameter, high-strength steel,
- ROPS-approved cage
- Adjustable driver's seat and tilt steering

- Passenger handhold and grab bar
   1,928 cu in. (31.6 L) of cockpit storage
   Digitally Encoded Security System (D.E.S.S.) anti-theft system, with 2 different keys
- Multifunction digital gauge



## **COLOR AND ENGINE OPTION**

Yellow - 1000

# **PACKAGE OPTION**

# X° rs PACKAGE

## **ADDED FEATURES**

- Front and rear FOX PODIUM X Performance RC2.5 HPG piggyback shocks with dual-speed compression, rebound and threaded preload adjustments
- 12-in. aluminum beadlock wheels
- Analog / digital gauge
- · Custom steering wheel with brushed-aluminum
- X-package seat trim and graphics

## **COLOR AND ENGINE OPTION**

Yellow & Black 1000 with X-package graphics





FOX PODIUM X Performance RC2.5 HPG piggyback shocks



Torsional Trailing A-arms (TTA) independent rear suspension



Rotax 1000R V-Twin engine with high-flow dynamics



12-in. aluminum beadlock wheels



X-package seat trim



X-package graphics



Cockpit

# **MAVERICK-GENUINE ACCESSORIES**







Whether you need them for dune or trail riding, all the accessories are built and designed by BRP to specifically match your vehicle, without compromises, increase comfort and versatility - and give you that unmistakable Can-Am look.



