EDEFENDER

IGHLIGHTS

- Heavy-duty Rotax® V-Twin engine options
- PRO-TORQ transmission
- TTA-HD rear suspension
- 12-in. (30.5 cm) steel wheels with 26-in. (66 cm) Maxxis M923J[†] tires
- VERSA-PRO bench seat
- Multifunction cargo box with sturdy tailgate
- Central skid plate
- Multifunction digital gauge
- 1-year maintenance free and easy access to key maintenance components

HD8 CONVENIENCE PACKAGE / HD10 ADDS:

- Lockable rear differential and Visco-Lok[‡] auto-locking front differential
- 10.4 gal (39.5 L) of storage capacity including a 1.7-gal (6.3 L) water-resistant toolbox and 6 gal (22.8 L) of under dash





-		
Green	/ HDX	/ HD10

ENGINES	HD8	HD10	
Туре	50 hp, Rotax 799.9 cc, V-twin, liquid cooled	72 hp, Rotax 976 cc, V-twin, liquid cooled	
Fuel Delivery System	Intelligent Throttle Control (iTC™)	with Electronic Fuel Injection (EFI)	
Transmission	PRO-TORQ transmission with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P		
Drive Train	Selectable 2WD / 4WD with Visco-Lok auto-locking front differential	True 4-mode traction system: 2x4 open rear dif., 2x4 locked rear dif., 4x4 open rear dif., 4x4 locked rear dif. Visco-Lok auto-locking front dif.	
Driving Assistance	Electronic Hill Descent Control		
Power Steering	N	/A	

SUSPENSIONS	
Front Suspension	Double A-arm / 10 in. (25.4 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	TTA-HD with external sway bar / 10 in. (25.4 cm) travel
Rear Shocks	Twin tube gas charged shocks

BRAKES	
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes with hydraulic single-piston calipers

DIMENSIONS /	CAPACITIES
LxWxH	120 x 62 x 76 in. (305 x 157.5 x 193 cm)
Wheelbase	83 in. (211.5 cm)
Ground Clearance	11 in. (28 cm)
Estimated Dry Weight	1,395 lb (632.7 kg)
Cage	ROPS-approved profiled cage. Certified ISO 3471 and OSHA.
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Cargo Box Capacity	1,000 lb (454 kg) / California only: 600 lb (272.2 kg)
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity [*]	Total: 10.4 gal (39.5 L) Under dash: 6 gal (22.8 L) Dash: 1.8 gal (6.9 L) Water-resistant and removable toolbox: 1.7 gal (6.3 L) Armrests and cup holders: 0.9 gal (3.5 L)
Towing Capacity	2,000 lb (907.2 kg)
Payload Capacity	1,500 lb (680 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	3

TIRES / WHEELS	
Front Tires	Maxxis M923J 26 x 9 x 12 in. (66 x 22.9 x 30.5 cm)
Rear Tires	Maxxis M924J 26 x 11 x 12 in. (66 x 27.9 x 30.5 cm)
Wheels	12-in. steel black

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip and hour meters,	Lighting	140-W lighting output from four 35-W reflectors ensuring a wide visiblity and LED tail lights
	fuel, gear position, seat belt, diagnostics, clock, auto shut off	Winch	N/A
	date shareon	Seat	VERSA-PRO bench seat with passenger seats flipping up, underside hooks and contoured bench to improve entrance/exit of the cab
Battery	12 V (18 amp/h)	Protection	Integrated front steel bumper, central skid plate
Magneto	650 W	Hitch Type	2-in. hitch receiver
Instrumentation	Lighter type DC outlet in console (20-A)	Steering Wheel	Adjustable tilt steering

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 30 months B.E.S.T. coverage

©2016 Bombardier Recreational Products Inc (BRP). All rights reserved. TM, © and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. "Visco-Lok is a trademark of GKM Viscodrive GmbH. 'All other trademarks are the property of their respective owners. *HD8 Convenience package/HD10 capacities shown. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.



