aOUTLANDER DPS™

HIGHLIGHTS

- Rotax® V-twin engine options
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Double A-arm front suspension with dive-control geometry
- Torsional Trailing arm Independent (TTI) rear suspension
- Visco-Lok[‡] QE auto-locking front differential
- 14-in. cast-aluminum wheels
- 230-W lighting from headlights
- 625-W magneto

- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- 5.7-gal (21.4 L) water-resistant rear compartment
- RF Digitally Encoded Security System (D.E.S.S.™)
- Multifunction digital gauge



Light Grey / 650 / 850 / 1000R

| ENGINES | 650 | 850 | 1000R |
|----------------------|--|--|--|
| Туре | 62 hp, Rotax 649.6 cc V-twin, liquid cooled | 78 hp, Rotax 854 cc V-twin, liquid cooled | 89 hp, Rotax 976 cc V-twin, liquid cooled |
| Fuel Delivery System | Electronic Fuel Injection (EFI) | | |
| Transmission | CVT, P / R / N / H / L, standard engine braking | | |
| Drive Train | Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential | | |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) | | |

| Fuel Delivery System | Electronic Fuel Injection (EFI) | |
|----------------------|--|--|
| Transmission | CVT, P / R / N / H / L, standard engine braking | |
| Drive Train | Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential | |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) | |
| SUSPENSIONS | | |
| Front Suspension | Double A-arm | |

| SUSPENSIONS | |
|------------------|--|
| Front Suspension | Double A-arm 9 in. (22.9 cm) travel |
| Front Shocks | 0il |
| Rear Suspension | Torsional Trailing arm Independent (TTI) 9.3 in. (23.6 cm) travel |
| Rear Shocks | Oil |

| BRAKES | |
|--------|--|
| Front | Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers |
| Rear | Single 214 mm ventilated disc brake with hydraulic twin-piston caliper |

| TIRES / WHEE | LS |
|--------------|--|
| Front Tires | ITP [†] Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm) |
| Rear Tires | ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm) |
| Wheels | 14-in. cast-aluminum |

| DIMENSIONS / CAPACITIES | | |
|-------------------------|---|--|
| LxWxH | 86 x 46 x 49.5 in. (218.4 x 116.8 x 126 cm) | |
| Wheelbase | 51 in. (129.5 cm) | |
| Ground Clearance | 11 in. (27.9 cm) | |
| Seat Height | 34.5 in. (87.7 cm) | |
| Engine / Dry Weight* | 650 / 726 lb (329 kg) 850 / 780 lb (354 kg) 1000R / 795 lb (361 kg) | |
| Rack Capacity | Front: 100 lb (45 kg) Rear: 200 lb (90 kg) | |
| Storage Capacity | Rear: 5.7 gal (21.4 L) | |
| Towing Capacity | 1,300 lb (590 kg) | |
| Fuel Capacity | 5.4 gal (20.5 L) | |

| FEATURES | | | |
|------------|--|-------------------|--|
| Gauge | Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom | Instrumentation | Lighter type DC outlet in console, standard connector in the back (15-A) |
| | bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, | Lighting | 230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light |
| | 4 x 4 indicator, temperature and engine rights, fuel gauge, clock | Seat | Standard |
| Winch | Prewired for available winch | Anti-theft System | RF Digitally Encoded Security System (D.E.S.S.) |
| Protection | N/A | | |

| WARRANTY | |
|----------|-----------------------------------|
| Factory | 6-months limited warranty |
| Extended | Up to 36 months B.E.S.T. coverage |



