## **ERENEGADE** X° mr 1000R

## HIGHLIGHTS

- Rotax® snorkeled V-Twin engine with relocated CVT intake and outlet
- Front and rear FOX<sup>†</sup> 1.5 PODIUM QS3 shocks
- 30-in. Gorilla Axle Silverback<sup>†</sup> tires
- 14-in. cast-aluminum beadlock wheels
- 3,000-lb (1,361 kg) WARN† winch with roller fairlead
- Aluminum skid plate
- Heavy-duty front and rear bumpers
- Aluminum taper-profile handlebar with grab handle, wind deflectors ans square pad
- Tri-Mode Dynamic Power Steering (DPS™)
- Continuously Variable Transmission (CVT) with Extra Low L-Gear
- Torsional Trailing arm Independent (TTI) rear suspension

- Mudguards
- Multifunction digital gauge
- Painted plastics for premium look
- X-package coloration, graphics and seat cover



Hyper Silver, Black & Can-Am Red / 1000R Hyper Silver, Black & Octane Blue / 1000R

ENGINE	1000R
Туре	89 hp, Rotax 976 cc V-twin, snorkeled, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE <sup>‡</sup> auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

Front Suspension	Double A-arm
Front Shocks	FOX 1.5 PODIUM QS3
Rear Suspension	Torsional Trailing arm Independent (TTI)
Rear Shocks	FOX 1.5 PODIUM QS3

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHEELS		
Front Tires	Gorilla Axle Silverback 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)	
Rear Tires	Gorilla Axle Silverback 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)	
Wheels	14-in. cast-aluminum beadlock	

DIMENSIONS / CAPACITIES			
LxWxH	83 x 50 x 56 in. (224 x 127 x 131 cm)		
Wheelbase	51 in. (129.5 cm)		
Ground Clearance	12.5 in. (31.8 cm)		
Seat Height	36.75 in. (93.3 cm)		
Engine / Dry Weight*	973 lb (441 kg)		
Rack Capacity	Rear: 35 lb (16 kg)		
Storage Capacity	N/A		
Towing Capacity	1,300 lb (590 kg)		
Fuel Capacity	5.4 gal (20.5 L)		

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom	Instrumentation	Lighter type DC outlet in console, standard connecto in the back (15-A)
	bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Lighting	240 W from 4 fender mounted projector beam headlamps (60 W) with tail light / brake light
		Seat	Standard
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Front & rear bumpers, aluminum taper-profile handlebar with grab handle, wind deflectors and square pads, aluminum skid plate, mudguards		

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage





Can-AmOffroad.com