

# 2014 OUTLANDER™ MAX



## STANDARD SPECIFICATIONS

ENGINE CHOICE	1000 DPS*	800R DPS*	650	500
Type	976 cc	799.9 cc	649.6 cc	499.6 cc
	V-twin, liquid-cooled, SOHC, 8-valve (4-valve / cyl)			
Bore & Stroke	91 x 75 mm	91 x 62 mm	82 x 62 mm	82 x 47 mm
EFI System / Carburetor	46 mm Throttle Body, 2 Siemens† VDO injectors			
Starting System	Electric			
Transmission	CVT, sub-transmission with high, low, park, neutral & reverse. Standard engine braking			
Drive Train	Selectable 2WD / 4WD shaft driven with Visco-Lok‡ auto-locking front differential*			

### CHASSIS

Frame	Surrounding Spar Technology (SST) G2			
Front Suspension Type / Shocks	Double A-arm			
Front Suspension Travel	9 in. (22.9 cm)			
Rear Suspension Type / Shocks	Torsional Trailing arm Independent (TTI)			
Rear Suspension Travel	9.3 in. (23.6 cm)			
Front Brake	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers			
Rear Brake	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper			
Tires / Front	Carlisle† Badland 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)			
Tires / Rear	Carlisle Badland 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)			
Wheels	Cast-aluminum	Cast-aluminum	Steel Black	Steel Black

### DRY WEIGHT

816 lb (371 kg)	796 lb (362 kg)	783 lb (356 kg)	777 lb (353 kg)
-----------------	-----------------	-----------------	-----------------

### DIMENSIONS

L x W x H (in.)	94 x 46 x 44 in.
L x W x H (cm)	238.8 x 116.8 x 111.8 cm
Wheelbase	59 in. (149.9 cm)
Seat Height	34.5 in. (87.7 cm)
Ground Clearance	11 in. (27.9 cm)
Towing Capacity	1,300 lb (590 kg)
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)
Storage	Rear: 5.7 gal (21.4 L) Convertible Rack System (CRS)
Fuel Capacity	5.4 gal (20.5 L)

### FEATURES

Instrumentation	Multifunction digital LCD gauge: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock, auto shut off
Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
Electrical	Prewired for winch
Lighting	230-W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
DC Outlet	Lighter type in console, standard connector in the back (15-A)

### WARRANTY

Factory	6 months limited warranty
Extended	B.E.S.T. available from 12 to 36 months



©2013 Bombardier Recreational Products Inc. (BRP). All rights reserved. \* With Visco-Lok QE on DPS model ‡ Visco-Lok is a trademark of GKN ViscoDrive GmbH. † All other trademarks are the property of their respective owners. Products are distributed in the U.S.A. by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. **ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain.** ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

**can-am**

can-am.brp.com



## STANDARD FEATURES

### OUTLANDER MAX

- Rotax® V-Twin engine options
- Continuously Variable Transmission (CVT) with engine braking
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Double A-arm front suspension with dive-control geometry
- Torsional Trailing arm Independent rear suspension (TTI)
- Visco-Lok auto-locking front differential
- Convertible Rack System (CRS) with LinQ™ system

- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- Raised floorboards
- High-strength, multipurpose racks with LinQ quick-attach accessory system
- 59-in. (149.9 cm) wheelbase
- 5.7-gal (21.4 L) water-resistant rear compartment
- 230-W lighting from headlights

#### COLOR AND ENGINE OPTIONS

Viper Red ■ 650 / 500



## PACKAGE OPTIONS

### OUTLANDER MAX DPS™

#### ADDED FEATURES

- Tri-Mode Dynamic Power Steering (DPS)
- Visco-Lok QE
- 12-in cast-aluminum wheels
- 625-W magneto

#### COLOR AND ENGINE OPTIONS

Yellow ■ 1000 / 800R / 650 / 500



### OUTLANDER MAX XT™

#### ADDED FEATURES

- Tri-Mode Dynamic Power Steering (DPS)
- Visco-Lok QE
- 12-in. cast-aluminum wheels with machined finish
- 26-in. Carlisle® ACT radial tires
- 3,000-lb (1,361 kg) WARN® winch with roller fairlead, wired remote control and integrated remote storage
- Heavy-duty front and rear bumpers
- Handlebar wind deflectors
- 625-W magneto

- Industry-exclusive NEXT G-1 Vista® Camo color option
- Pure Magnesium Metallic painted plastic color option

#### COLOR AND ENGINE OPTIONS

Viper Red ■ 800R / 650 / 500

Yellow ■ 1000 / 800R / 650 / 500

Pure Magnesium Metallic ■ 1000 / 800R / 650

Camo ■ 1000 / 800R / 650



### OUTLANDER MAX XT-P

#### ADDED FEATURES

- Front and rear FOX® PODIUM® X Performance RC2.0 HPG Piggyback shocks
- Tri-Mode Dynamic Power Steering (DPS)
- Visco-Lok QE
- 12-in. cast-aluminum beadlock wheels
- 26-in. Carlisle ACT radial tires
- 3,000-lb (1,361 kg) WARN winch with roller fairlead, wired remote control and integrated remote storage
- Heavy-duty front & rear bumpers

- Aluminum taper-profile handlebar with wind deflectors and square pad
- Black painted plastic
- 625-W magneto
- Analog / digital gauge

#### COLOR AND ENGINE OPTIONS

Black & Yellow ■ 1000 / 800R



### OUTLANDER MAX LIMITED

#### ADDED FEATURES

- Rear Air Control Suspension (ACS) with FOX Air Assist HPG shocks
- Tri-Mode Dynamic Power Steering (DPS)
- Visco-Lok QE
- Garmin® Montana® 650t touchscreen GPS
- 12-in. cast-aluminum wheels with machined finish
- 26-in. Carlisle ACT radial tires
- 3,000-lb (1,361 kg) WARN winch with roller fairlead, wired remote control and integrated remote storage
- Heavy-duty front & rear bumpers

- Mudguards
- Handlebar wind deflectors
- Premium 2-tone seat
- Comfort grips
- 625-W magneto
- Analog / digital gauge
- Painted plastics

#### COLOR AND ENGINE OPTIONS

Pure Magnesium Metallic ■ 1000

Pearl White □ 1000





# 2014 OUTLANDER™ MAX—GENUINE ACCESSORIES

## FRONT & REAR LINQ RACK EXTENSIONS

These strong, durable rack extensions install easily on the Outlander and Outlander MAX thanks to the LinQ System, requiring no tools. It helps keep your cargo more securely in place.



## LINQ 124 L TRUNK BOX FOR MAX

Specifically designed for the Outlander MAX. Extra large, innovative LinQ System mount, with passenger comfort pads and rear tail light. Weather-resistant lid gaskets seal out dust and moisture. Key locking latch. Color panels available to match your vehicle.



## FRONT & REAR BUMPERS

Provide additional protection against the elements. Tough and durable, they can be added on the vehicle to give your Outlander the look of an XT model.

## PASSENGER HEATED HAND GRIPS AND WIND DEFLECTORS

Passenger handles with dual temperature and visor outlet, plus wind deflectors for greater comfort while riding.

## UNDERBELLY PROTECTION

Aluminum plates made with high strength 5052 H32 aluminum and plastic deflector to protect your frame from the unexpected. A must-have for rugged terrains.

## EXTRA HIGH WINDSHIELD

For wind protection and winter applications.

## DELUXE FAIRING

The Deluxe Fairing provides not only wind protection, but a series of innovative features:

- Quick tool-less removal once the base brackets are mounted on the handlebar
- 2 cup holders
- Optional GPS mounting kit
- Optional windshield can be added on
- Optional mirrors
- Optional auxiliary windshield lighting



Shop at  
**store.can-am.brp.com**  
or at your authorized Can-Am dealer.

**can-am**

