

HIGHLIGHTS

DARING	<ul style="list-style-type: none"> Sturdy engine and transmission Enhanced comfort and meaningful functionalities Can-Am design
PRECISE	<ul style="list-style-type: none"> Easy handling and capabilities Suspension designed for performance Ultra-resistant chassis
CAPABLE	<ul style="list-style-type: none"> Work or ride with confidence Meaningful and versatile functionality Easy handling and capabilities
PLATFORM FEATURES	<ul style="list-style-type: none"> 120.6 in. wheelbase 13 in. ground clearance 15 in. suspension travel 2,000 lb towing capacity Dynamic Power Steering (DPS™) Visco-Lok[†] QE front differential SPORT/ECO™ modes D.E.S.S. key with Start/Stop button Premium half doors Mudguards Rear differential with Turf mode
SPECIFIC TO XT PACKAGE	<ul style="list-style-type: none"> 64 in. wide with arched double A-arm 28 in. XPS Trail King tires 14 in. cast-aluminum wheels XT front bumper 4,500 lb (2,014 kg) winch 7.6 in. digital display with keypad Can-Am LED signature Painted color options

ENGINE	1000R
Type	100 hp, Rotax [®] 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L/H/N/R/P
Drive Train	Selectable Turf Mode/2WD/4WD with Visco-Lok [†] QE auto-locking front differential
Driving Assistance	Electronic Hill Descent Control SPORT/ECO™ modes
Power Steering	Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Arched double A-arm with sway bar/15 in. (38.1 cm) travel
Front Shocks	Twin-tube gas-charged shocks
Rear Suspension	Arched TTA with sway bar/15 in. (38.1 cm) travel
Rear Shocks	Twin-tube gas-charged shocks

TIRES & WHEELS

Front Tires	XPS Trail King 28 x 9 x 14 in. (71.1 x 22.9 x 35.6 cm)
Rear Tires	XPS Trail King 28 x 11 x 14 in. (71.1 x 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

BRAKES

Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers



Oxford Blue / 1000R

DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,930 lb (875.4 kg)
Chassis/Cage	Profiled cage ROPS approved
L x W x H	160 x 64 x 74 in (406.7 x 162.6 x 188.2 cm)
Wheelbase	120.6 in. (306.3 cm)
Ground Clearance	13 in. (33 cm)
Cargo Box Dimensions	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)
Cargo Box Capacity	600 lb (272.2 kg)
Towing Capacity	2,000 lb (907.2 kg)
Payload Capacity	1,280 lb (580.6 kg)
Storage Capacity	Total: 8.5 gal (32.1 L) Glove box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and cup holders: 0.8 gal (3.1 L) Rear console and cup holders: 1.2 gal (4.5 L) Side cargo box storage (passenger side): 1.6 gal (5.9 L) Dual side panel storage: 0.8 gal (3.0 L)
Fuel Capacity	10 gal (38 L)

FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature
Instrumentation	Lighter-type DC outlet in console (10 A)
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Magneto	650 W
Lighting	Two 55 W reflectors headlights with unique Can-Am LED signature and LED taillights
Winch	4,500 lb (2,041 kg) winch with roller fairlead
Steering Wheel	Adjustable tilt steering
Protection	Premium half doors Full skid plate Mudguards XT front bumper
Hitch Type	2 in. hitch receiver

WARRANTY

Factory Warranty	2 years BRP limited warranty
------------------	------------------------------