

MAVERICK X3 X rc TURBO RR 72"

HIGHLIGHTS

DEFIANT	• Trademark Can-Am DNA with next-generation design • Low seating position • Ergo-Lok cockpit with four-way adjustable seats
POWERFUL	• Industry-leading 200 hp turbocharged and intercooled Rotax® ACE engine • Advanced airflow dynamics • QRS-X transmission
PRECISE	• TTX suspension with industry-leading travel • Ultra efficient and lightweight chassis • Sharpest handling features
PLATFORM FEATURES	• 72.8 in. (184.9 cm) wide • 102 in. (259.1 cm) wheelbase • 16 in. (40.6 cm) of ground clearance • High-torque Dynamic Power Steering (DPS™) • Up to 24 in. (61 cm) of suspension travel • Rear tow hook
SPECIFIC TO X rc TURBO RR 72" PACKAGE	• Belt-monitoring system • 200 hp Turbo RR engine • Smart-Lok™* front differential • FOX 3.0 PODIUM RC2 shocks with bypass • 15 in. (162.6 cm) aluminum beadlock wheels • 32 in. Maxxis Liberty tyres • Front bumper, half-doors, aluminum roof, intrusion bar • Front tow hook • HMWPE differential and under-bumper skid plates • HMWPE front and rear suspension arm • UHMWPE rock sliders • 4,500 lb (2,041 kg) winch with synthetic rope • 4-point harness with shoulder pads • X-package graphics/seats • 7.6 in. digital display with keypad • Can-Am LED signature • 850 W magneto • Painted color



Chalk Gray & Magma Red / TURBO RR

DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,843 lb (836 kg)
Chassis/Cage	Dual-phase 980 steel
L x W x H	134.5 x 72.8 x 68.5 in. (341.6 x 184.9 x 174 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)

FEATURES

Gauge	7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Instrumentation	Lighter-type DC outlet in central console
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	4,500 lb (2,041 kg) winch with synthetic rope
Magneto	850 W
Protection	Front bumper Half doors Aluminum roof Intrusion bar 4-point harness with shoulder pads UHMWPE rock sliders HMWPE skidplates: Full heavy-duty with differential/Under bumper/ Front and rear suspension arm Rear tow hook

WARRANTY & SERVICE

Factory Warranty	2 years/ 15,000 km warranty, whichever comes first
------------------	--

ENGINE	TURBO RR
Type	200 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD ROCK/4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Trophy truck-inspired arched double A-arm with sway bar/22 in. (55.9 cm) travel
Front Shocks	FOX 2.5 PODIUM RC2 piggyback with bypass, dual speed compression and rebound adjustments
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links/24 in. (61 cm) travel
Rear Shocks	FOX 3.0 PODIUM RC2 remote reservoir with bypass, dual speed compression and rebound adjustments

TYRES & WHEELS

Front Tyres	Maxxis Liberty 32 x 10 x 15 in.
Rear Tyres	Maxxis Liberty 32 x 10 x 15 in.
Wheels	15 in. cast-aluminum beadlock

BRAKES

Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers