

DEFENDER MAX XT HD10

HIGHLIGHTS

TOUGH	<ul style="list-style-type: none"> • Heavy-duty Rotax® engine • Smooth, durable and responsive transmission • True Can-Am DNA with a strong identity
CAPABLE	<ul style="list-style-type: none"> • Work or ride with confidence • Meaningful and versatile functionality • Easy handling and capabilities
CLEVER	<ul style="list-style-type: none"> • Advanced comfort and intuitive cockpit with optimized visibility • Multifunction cargo box with sturdy tailgate and smart storage • 1 year maintenance-free and easy access to key maintenance components
PLATFORM FEATURES	<ul style="list-style-type: none"> • 115.5 in. (294 cm) wheelbase • 12.5 in. (31.8 cm) of ground clearance • Dynamic Power Steering (DPS) • 2,500 lb (1,134 kg) towing capacity • Multifunction cargo box • 27 in. Maxxis Bighorn 2.0 • Rear differential with Turf mode • 4.5 in. digital display
SPECIFIC TO MAX XT package	<ul style="list-style-type: none"> • 64 in. (162.5 cm) wide with Arched A-arm • Visco-Lok QE front differential • 14 in. cast-aluminum wheels • VERSA-PRO bolster bench seats with reinforced XT seat skin and adjustable driver seat • HMWPE full skid plate • 4,500 lb (2,014 kg) winch • XT front bumper • Full hard roof • Brake holding mechanism

ENGINE	HD10
Type	82 hp/69 lb-ft, Rotax® 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ CVT Transmission with Quick Response System (QRS), high-airflow ventilation and Electronic Drive Belt Protection Extra L/H/N/R/P
Drive Train	Selectable Turf Mode / 2WD/4WD with Visco-Lok [†] QE auto-locking front differential
Driving Assistance	Electronic Hill Descent Control ECO™/ECO™ Off/Work modes
Power Steering	Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Arched double A-arm/11 in. (27.9 cm) travel
Front Shocks	Twin tube gas-charged shocks
Rear Suspension	Arched TTA with external sway bar/11 in. (27.9 cm) travel
Rear Shocks	Twin tube gas-charged shocks

Tyres & WHEELS

Front Tyres	Maxxis Bighorn 2.0 27 x 9 x 14 in.
Rear Tyres	Maxxis Bighorn 2.0 27 x 11 x 14 in.
Wheels	14 in. cast-aluminum

BRAKES

Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers
	Brake-holding mechanism



Asphalt Grey / HD10

DIMENSIONS & CAPACITIES

Chassis/Cage	Profiled cage, ROPS approved
Estimated Dry Weight	1,902.6 lb (863 kg)
L x W x H	158.3 x 64 x 79.5 in. (402 x 162.5 x 202 cm)
Wheelbase	115.5 in. (294 cm)
Ground Clearance	12.5 in. (31.8 cm)
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Cargo Box Capacity	1,000 lb (454 kg)/California only: 600 lb (272.2 kg)
Power Tilt Bed	N/A
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Total: 16.9 gal (63.9 L) Under dash: 6 gal (22.8 L) Waterproof and removable box under passenger seat: 5.6 gal (21 L) Dash: 2 gal (7.7 L) Water-resistant and removable toolbox: 1.7 gal (6.3 L) Armrests and cup holders: 1.6 gal (6.1 L)
Towing Capacity	2,500 lb (1,134 kg)
Payload Capacity	1,750 lb (793.8 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	6

FEATURES

Gauge	4.5 in. wide digital display: speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, ECO™/ECO™ Off/Work modes, seat belt, diagnostics, clock, battery voltage, engine temperature
Battery	12 V (30 amp/h)
Magneto	650 W
Instrumentation	Lighter-type DC outlets in the console (10 A) and two lighted USB port in the dash storage (10 A)
Lighting	140 W lighting output from four 35 W reflectors ensuring a wide visibility and LED tail lights
Winch	4,500 lb (2,041 kg) winch with roller fairlead
Seat	Dual VERSA-PRO bolster bench seats for additional lateral support with passenger seats flipping up, adjustable driver seat, underside hooks, reinforced XT seat skin and contoured bench to improve entrance/exit of the cab
Steering Wheel	Adjustable tilt steering
Protection	XT front bumper, HMWPE full skid plate, 2-piece full hard roof
Hitch Type	2 in. hitch receiver

WARRANTY & SERVICE

Factory Warranty	2 years/ 15,000 km warranty, whichever comes first
Service Intervals	200 hrs / 12 months / 3,000 km