

## MAVERICK X3 DS TURBO

### HIGHLIGHTS

<b>DEFIANT</b>	<ul style="list-style-type: none"> <li>• Trademark Can-Am DNA with next generation design</li> <li>• Low seating position</li> <li>• Ergo-Lok cockpit with four-way adjustable seats</li> </ul>
<b>POWERFUL</b>	<ul style="list-style-type: none"> <li>• 120 hp turbocharged Rotax® ACE engine</li> <li>• Advanced airflow dynamics</li> <li>• QRS-X transmission</li> </ul>
<b>PRECISE</b>	<ul style="list-style-type: none"> <li>• TTX suspension with industry-leading travel</li> <li>• Ultra efficient and lightweight chassis</li> <li>• Sharpest handling features</li> </ul>
<b>PLATFORM FEATURES</b>	<ul style="list-style-type: none"> <li>• 64 in. (162.5 cm) wide</li> <li>• 102 in. (259.1 cm) wheelbase</li> <li>• 14 in. (35.6 cm) of ground clearance</li> <li>• High-torque Dynamic Power Steering (DPS™)</li> <li>• 20 in. (50.8 cm) suspension travel</li> <li>• FOX 2.5 PODIUM QS3 piggyback shocks</li> <li>• 14 in. aluminum wheels</li> <li>• 30 in. Maxxis Carnivore tyres</li> <li>• 4.5 in. digital display with keypad</li> <li>• Rear tow hook</li> </ul>



Octane Blue / TURBO

ENGINE	TURBO
Type	120 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok* technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD TRAIL ACTIV/4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm with sway bar/20 in. (50.8 cm) travel
Front Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar/20 in. (50.8 cm) travel
Rear Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment and bottom-out control

TYRES & WHEELS	
Front Tyres	Maxxis Carnivore 30 x 10 x 14 in.
Rear Tyres	Maxxis Carnivore 30 x 10 x 14 in.
Wheels	14 in. cast-aluminum

BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers

### DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,546 lb (701.3 kg)
Chassis/Cage	Dual-phase 980 steel
L x W x H	132 x 64 x 65.4 in. (335.3 x 162.5 x 166.1 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	14 in. (35.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)

### FEATURES

Gauge	4.5 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Instrumentation	Lighter-type DC outlet in central console
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights and tail lights
Winch	N/A
Magneto	650 W
Protection	Integrated front bumper Quarter doors HMWPE full skid plate Rear tow hook

### WARRANTY & SERVICE

Factory Warranty	2 years/ 15,000 km warranty, whichever comes first
------------------	--