

MAVERICK X3 MAX X rs TURBO RR

HIGHLIGHTS

DEFIANT	<ul style="list-style-type: none"> • Trademark Can-Am DNA with next-generation design • Low seating position • Ergo-Lok cockpit with front and rear four-way adjustable seats
POWERFUL	<ul style="list-style-type: none"> • Industry-leading 200 hp turbocharged and intercooled Rotax[®] ACE engine • Advanced airflow dynamics • QRS-X transmission
PRECISE	<ul style="list-style-type: none"> • TTX suspension with industry-leading travel • Ultra efficient and lightweight chassis • Sharpest handling features
PLATFORM FEATURES	<ul style="list-style-type: none"> • 72.7 in. (184.7 cm) wide • 135 in. (342.9 cm) wheelbase • 16 in. (40.6 cm) of ground clearance • High-torque Dynamic Power Steering (DPS[™]) • 22 in. (55.9 cm) suspension travel • Rear tow hook
SPECIFIC TO X rs TURBO RR PACKAGE	<ul style="list-style-type: none"> • Belt-monitoring system • 200 hp Turbo RR engine • Smart-Lok[™]* front differential • FOX 3.0 PODIUM RC2 shocks with bypass • 14 in. aluminum beadlock wheels • 32 in. Maxxis Carnivore[†] tyres • 4-point harness with shoulder pads • HMWPE full skid plate • Full roof • X-package graphics/seats • 7.6 in. digital display with keypad • Can-Am LED signature • 850 W magneto



■ Intense Blue, Carbon Black & Chalk Gray / TURBO RR

DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,924 lb (872.7 kg)
Chassis/Cage	Dual-phase 980 steel
L x W x H	165 x 72.7 x 68.5 in. (419.1 x 184.7 x 174 cm)
Wheelbase	135 in. (342.9 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	150 lb (68 kg) with LinQ [™] quick-attach
Storage Capacity	Total: 3 gal (11.4 L) Glove box: 1.6 gal (6.2 L) Central console: 1.1 gal (4.1 L) Cup holders: 0.3 gal (1.1 L)
Fuel Capacity	10.5 gal (40 L)

FEATURES

Gauge	7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO [™] mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Instrumentation	Lighter-type DC outlet in central console
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S. [™]) with Start/Stop button
Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	N/A
Magneto	850 W
Protection	Integrated front bumper Quarter-doors Full roof 4-point harness with shoulder pads HMWPE full skid plate Rear tow hook

WARRANTY & SERVICE

Factory Warranty	2 years/15,000 km warranty, whichever comes first
------------------	---

ENGINE	TURBO RR
Type	200 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC [™]) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD TRAIL ACTIV/4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Double A-arm with sway bar/22 in. (55.9 cm) travel/Trophy truck-inspired arms
Front Shocks	FOX 2.5 PODIUM RC2 piggyback with bypass, dual speed compression and rebound adjustments
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar/22 in. (55.9 cm) travel
Rear Shocks	FOX 3.0 PODIUM RC2 remote reservoir with bypass, dual speed compression and rebound adjustments

TYRES & WHEELS

Front Tyres	Maxxis Carnivore 32 x 10 x 14 in.
Rear Tyres	Maxxis Carnivore 32 x 10 x 14 in.
Wheels	14 in. cast-aluminum beadlock

BRAKES

Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers