

OUTLANDER™ 650 H.O. EFI



**Outlander
650 H.O. EFI 4x4**



**Outlander
650 H.O. EFI XT 4x4**



**Outlander MAX
650 H.O. EFI 4x4**



**Outlander MAX
650 H.O. EFI XT 4x4**

Revised May 05, 2006

	SPECIFICATIONS	OUTLANDER 650 H.O. EFI 4X4	OUTLANDER MAX 650 H.O. EFI 4X4
ENGINE	Type	650cc, 4-stroke, V-twin, liquid-cooled, 8-valve SOHC	650cc, 4-stroke, V-twin, liquid-cooled, 8-valve SOHC
	Bore & Stroke	82 x 62 mm	82 x 62 mm
	Torque	58 Nm @ 5,500 RPM	58 Nm @ 5,500 RPM
	Fuel Delivery	EFI, 46mm Throttle Body, 2 Siemens [†] VDO injectors	EFI, 46mm Throttle Body, 2 Siemens [†] VDO injectors
	Starting System	Electric	Electric
	Transmission	CVT, sub-transmission with high, low, park, neutral & reverse	CVT, sub-transmission with high, low, park, neutral & reverse
CHASSIS	Drive Train	Selectable 2x4/4x4 shaft driven with Visco-Lok [†] front differential	Selectable 2x4/4x4 shaft driven with Visco-Lok [†] front differential
	Frame	SST	SST
	Front Suspension Type	Double A-arm, Forged Aluminum upper arm, 8 in (203 mm)	Double A-arm, Forged Aluminum upper arm, 8 in (203 mm)
	Travel		
	Rear Suspension Type	TTL independent	TTL independent
	Travel	9 in (229 mm)	9 in (229 mm)
DIMENSIONS	Front Brake	2 inboard hydraulic discs	2 inboard hydraulic discs
	Rear Brake	1 inboard hydraulic disc	1 inboard hydraulic disc
	Tires /Front	26 x 8 x 12 in (660 x 203 x 305 mm)	26 x 8 x 12 in (660 x 203 x 305 mm)
	Tires /Rear	26 x 10 x 12 in (660 x 254 x 305 mm)	26 x 10 x 12 in (660 x 254 x 305 mm)
	Wheels	Steel (Camo: painted black steel)	Steel (Camo: painted black steel)
FEATURES	L x W x H	86 x 46 x 45 in (2,184 x 1,168 x 1,143 mm)	94 x 46 x 45 in (2,387 x 1,168 x 1,143 mm)
	Wheelbase	51 in (1,295 mm)	59 in (1,499 mm)
	Dry Weight	649 lbs (295 kg)	699 lbs (318 kg)
	Ground Clearance	12 in (305 mm)	12 in (305 mm)
	Seat Height	34.5 in (877 mm)	34.5 in (877 mm)
	Rack Capacity	Front: 100 lbs (45 kg) Rear: 200 lbs (90 kg)	Front: 100 lbs (45 kg) Rear: 200 lbs (90 kg)
	Towing Capacity	1,300 lbs (590 kg)	1,300 lbs (590 kg)
	Fuel Capacity	5.3 US gal (20L)	5.3 US gal (20L)
	Instrumentation	Multi-function gauge: Speedometer, tachometer, odometer, trip and hourmeter, fuel, gear position, 4x4 indicator, diagnostics, auto shut off	Multi-function gauge: Speedometer, tachometer, odometer, trip and hourmeter, fuel, gear position, 4x4 indicator, diagnostics, auto shut off
	Anti-theft	D.E.S.S. (digital encoded security system)	D.E.S.S. (digital encoded security system)
	Storage	Rear storage 5.3 US gal (20L)	Rear storage 5.3 US gal (20L) CRS (Convertible Rack System)
	Electrical	Prewired for winch	Prewired for winch
	Lighting	2 fender mounted headlamps (35W) with tail light/brake light	2 fender mounted headlamps (35W) with tail light/brake light
	DC Outlet	Lighter-type in console, Standard connector at the back (15A)	Lighter-type in console, Standard connector at the back (15A)
	XT Package Content Available	BRP XL2500 winch by Warn [†] , roller fairlead, wired remote control, cast aluminum rims (except Camo), aggressive tread Carlisle [†] ACT radial tires, heavy duty front & rear bumpers, handlebar guards	BRP XL2500 winch by Warn [†] , roller fairlead, wired remote control, cast aluminum rims (except Camo), aggressive tread Carlisle [†] ACT radial tires, heavy duty front & rear bumpers, handlebar guards
	Colors	Yellow, Laurentian Green, Viper Red, Camo	Yellow, Laurentian Green, Viper Red, Camo

©2006 Bombardier Recreational Products Inc. (BRP). All rights reserved. [™] and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. Visco-Lok is a trademark of GKN ViscoDrive GmbH. [†] All other trademarks are the property of their respective owners. Products are distributed in the USA by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S., call the ATV Safety Institute at 1(800) 887-2887. In Canada, call the Canadian Safety Council at 1(613) 739-1535 ext. 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol/drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Can-Am[™] Outlander MAX ATVs: These ATVs are recommended for drivers aged 16 and older, and passengers aged 12 and older only.

can-am
THE ULTIMATE RIDE[™]

