agoutlander XT™

HIGHLIGHTS

- Rotax® V-twin engine options
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 3,000-lb (1,361 kg) WARN[†] winch with roller fairlead
- · Heavy-duty front and rear bumpers
- Handlebar wind deflectors
- Painted plastics for premium look
- 14-in. cast-aluminum wheels
- 26-in. ITP† Terracross radial tires
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Double A-arm front suspension with dive-control geometry

- Torsional Trailing arm Independent (TTI) rear suspension
- 625-W magneto
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- 5.7-gal (21.4 L) water-resistant rear compartment



Brushed Aluminum / 650 / 850 / 1000R

Pearl White & Black / 650 / 850 / 1000R

Mossy Oak† Break-Up Country Camo† / 650 / 850

ENGINES	650	850	1000R	
Туре	62 hp, Rotax 649.6 cc V-twin, liquid cooled	78 hp, Rotax 854 cc V-twin, liquid cooled	89 hp, Rotax 976 cc V-twin, liquid cooled	
Fuel Delivery System	Electronic Fuel Injection (EFI)			
Transmission	CVT, P / R / N / H / L, standard engine braking			
Drive Train	Selectable 2WD / 4WD with Visco-Lok‡ QE auto-locking front differential			
Power Steering	Tri-Mode Dynamic Power Steering (DPS)			

SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	0il
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.3 in. (23.6 cm) travel
Rear Shocks	0il

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEELS	
Front Tires	ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)
Rear Tires	ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)
Wheels	14-in. cast-aluminum

DIMENSIONS / CAPACITIES		
LxWxH	86 x 46 x 49.5 in. (218.4 x 116.8 x 126 cm)	
Wheelbase	51 in. (129.5 cm)	
Ground Clearance	11 in. (27.9 cm)	
Seat Height	34.5 in. (87.7 cm)	
Engine / Dry Weight*	650 / 726 lb (329 kg) 850 / 780 lb (354 kg) 1000R / 795 lb (361 kg)	
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)	
Storage Capacity	Rear: 5.7 gal (21.4 L)	
Towing Capacity	1,300 lb (590 kg)	
Fuel Capacity	5.4 gal (20.5 L)	

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Standard
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Heavy-duty front & rear bumpers,		

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage



handlebar wind deflectors

