

2019 OUTLANDER™ X® mr 850

HIGHLIGHTS

- Rotax® V-twin engine
- New arched double A-arm front suspension with front sway bar
- 30-in. ITP Cryptid[†] tires
- 14-in. cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS™)
- Front and rear FOX[†] PODIUM[†] 1.5 shocks
- Visco-Lok[†] QE auto-locking front differential
- Relocated radiator
- 3,000-lb (1,361 kg) WARN[†] winch with roller fairlead
- Heavy-duty front bumper
- Mud-riding footrests
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Torsional Trailing arm Independent (TTI) rear suspension
- 625-W magneto
- X-package coloration, graphics and seat cover



Sunburst Yellow / 850

ENGINE

850

Type	78 hp, Rotax 854 cc V-twin, snorkeled, liquid cooled with relocated radiator
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar
Front Shocks	FOX [†] PODIUM [†] 1.5
Rear Suspension	Torsional Trailing arm Independent (TTI)
Rear Shocks	FOX [†] PODIUM [†] 1.5

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEELS

Front Tires	ITP Cryptid [†] 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Rear Tires	ITP Cryptid [†] 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Wheels	14-in. cast-aluminum

DIMENSIONS / CAPACITIES

L x W x H	88 x 50 x 51.5 in. (224 x 127 x 131 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	13 in. (33 cm)
Seat Height	36.75 in. (93.3 cm)
Dry Weight	990 lb (450 kg)
Rack Capacity	Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,650 lb (750 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Protection	Heavy-duty front bumper, mud-riding footrests	Seat	Standard
		Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)

WARRANTY

Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage

BEST PROTECTION ©2018 Bombardier Recreational Products Inc. (BRP). All rights reserved.™ ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. "Visco-Lok" is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

can-am.

Can-AmOffroad.com

