©OUTLANDER™ X™ xc

HIGHLIGHTS

- Rotax® V-twin engine
- Intelligent Throttle Control (iTC™) with riding modes
- Front and rear FOX† PODIUM† 1.5 RC2 shocks
- 14-in. cast-aluminum beadlock wheels
- 26-in. ITP[†] Terracross radial tires
- Sport bumper with aluminum pre-runner
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- Front, center & footwell aluminum skid plates
- HMWPE A-arms protectors
- Aluminum taper-profile handlebar with wind deflectors and square pad
- 625-W magneto

- High-strength, multifunction racks with LinQ[™] quick-attach accessory system
- 5.7-gal (21.4 L) water-resistant rear compartment
- Multifunction Analog / Digital gauge
- X package coloration
- Separate front & rear brake controls



Black, Hyper Silver & Sunburst Yellow / 1000R

ENGINE	1000R
Туре	91 hp, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC TM) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok [‡] QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3cm) travel
Front Shocks	FOX† PODIUM† 1.5 RC2
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel
Rear Shocks	FOX† PODIUM† 1.5 RC2

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEEL	S
Front Tires	ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6cm)
Rear Tires	ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)
Wheels	14-in. cast-aluminum beadlock

DIMENSIONS / CAPACITIES				
LxWxH	86 x 48 x 49.5 in. (218.4 x 121,9 x 126 cm)			
Wheelbase	51 in. (129.5 cm)			
Ground Clearance	11 in. (27.9 cm)			
Seat Height	34.5 in. (87.7 cm)			
Dry Weight	826 lb (375 kg)			
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)			
Storage Capacity	Rear: 5.7 gal (21.4 L)			
Towing Capacity	1,650 lb (750 kg)			
Fuel Capacity	5.4 gal (20.5 L)			

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Standard
Winch	Prewired for available winch	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Front bumper with pre-runner Aluminum taper-profile handlebar with wind deflectors and square pad Front, center & footwell aluminum skid plates		

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage



HMWPE A-arms protectors, mudguards

