## **©OUTLANDER™ MAX XT 570**

## HIGHLIGHTS

- Rotax® V-Twin engine
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 3,000-lb (1,361 kg) WARN† winch with roller
- Heavy-duty front and rear bumpers
- Painted plastics for premium look
- 12-in. cast-aluminum wheels
- 25-in. Maxxis† M923J radial tires
- Torsional Trailing arm Independent (TTI) rear suspension
- · Wind deflectors

- Steel racks with LinQ quick-attach accessory system and a combined 360 pounds (163.3 kg) capacity
- 2.9-gal (10.9 L) water-resistant rear compartment
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- · Raised floorboards



ENGINE	570
Туре	48 hp, Rotax 570 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE <sup>‡</sup> auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

Front Suspension	Double A-arm 9 in. (22.9 cm) travel	
Front Shocks	Oil	
Rear Suspension	Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel	
Rear Shocks	Oil	

Tront Suspension	9 in. (22.9 cm) travel	
Front Shocks	Oil	
Rear Suspension	Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel	
Rear Shocks	Oil	
BRAKES		
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers	
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper	

Maxxis M923J 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Maxxis M923J 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
12-in. cast-aluminum

DIMENSIONS / CAPACITIES			
LxWxH	91 x 46 x 52.5 in. (231 x 116.8 x 133 cm)		
Wheelbase	59 in. (149.9 cm)		
Ground Clearance	10.5 in. (26.7 cm)		
Seat Height	33.8 in. (85.8 cm)		
Dry Weight	741 lb (336 kg)		
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)		
Storage Capacity	Rear: 2.9 gal (10.9 L)		
Towing Capacity	1,300 lb (590 kg)		
Fuel Capacity	5.4 gal (20.5 L)		

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer,	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Lighting	70 W from dual 35-W front light / brake light
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Seat	Convertible Rack System (CRS)
Protection	Heavy-duty front & rear bumpers Handlebar wind deflectors	Anti-theft System	N/A

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage

