

2019 RENEGADE®

HIGHLIGHTS

- Rotax® V-twin engine options
- New arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with engine braking
- 12-in. cast-aluminum wheels
- 25-in. ITP Holeshoot® ATR tires
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Torsional Trailing arm Independent (TTI) rear suspension
- Visco-Lok® auto-locking front differential
- Multifunction digital gauge
- Separate front and rear brake controls
- RF Digitally Encoded Security System (D.E.S.S.™)



Sunburst Yellow / 570 / 850 / 1000R

ENGINES	570	850	1000R
Type	48 hp, Rotax 570 cc V-twin, liquid cooled	78 hp, Rotax 854 cc V-twin, liquid cooled	91 hp, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)		Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking		
Drive Train	Selectable 2WD / 4WD with Visco-Lok auto-locking front differential		
Power Steering	N/A		

SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3cm) travel	
Front Shocks	Oil	FOX† PODIUM† 1.5
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel	
Rear Shocks	Oil	FOX† PODIUM† 1.5

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for available winch	Lighting	240 W from 4 fender mounted projector beam headlamps (60-W) with tail light / brake light
Protection	Front bumper, optional wind deflectors	Seat	Standard
		Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.)

WARRANTY

Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage

TIRES / WHEELS

Front Tires	ITP Holeshoot ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	ITP Holeshoot ATR 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS / CAPACITIES

L x W x H	86 x 48 x 49 in. (218.4 x 121.2 x 124 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	10.5 in. (26.7 cm)
Seat Height	34.5 in. (87.7 cm)
Engine / Dry Weight*	570 / 628 lb (286 kg) 850 / 681 lb (310 kg) 1000R / 710 lb (323 kg)
Rack Capacity	Rear: 35 lb (16 kg)
Storage Capacity	N/A
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

BEST PROTECTION ©2018 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US, Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GMI Viscodrive GmbH. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext. 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

can-am.

Can-AmOffroad.com

