FFNDFR X

PLATFORM FEATURES

- 83-in. wheelbase

- os-in. Wheeldase 13-in. of ground clearance Dynamic Power Steering (DPS™) ECO™ / ECO Off / Work modes 2,500 lb towing capacity
- Multi-function cargo box with LinQ easy installation accessories

TOUGH

Rear differential with Turf mode

SPECIFIC TO XT-P PACKAGE

- 64-in. wide with Arched A-arm
- Visco-Lok[‡] QE front differential
- 14-in. cast-aluminum wheels VERSA-PRO bench seat with reinforced bolster seat and adjustable driver seat
- HMWPE full skid plate 4,500-lb (2,014 kg) winch
- Heavy-duty front steel bumper
- Full hard roof
- Aluminum rock slider
- 7.6 in. digital display with keypad

Easy handling and capabilities

Brake holding mechanism

CAPABLE

- Heavy-duty Rotax® engine Smooth, durable and responsive
- transmission
 - True Can-Am DNA with a strong

CLEVER

- · Work or ride with confidence · Advanced comfort and intuitive Meaningful and versatile cockpit with optimized visibility functionality
 - Multifunction cargo box with sturdy tailgate and smart storage
 - 1-year maintenance free and easy access to key maintenance components



Carbon Black & Platinum Satin / HD10

ENGINE	HD10			
Туре	82 hp / 69 lb-ft, Rotax® 976 cc, V-twin, liquid cooled			
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)			
Transmission	PRO-TORQ Transmission with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P			
Drive Train	Selectable Turf Mode / 2WD / 4WD with Visco-Lok QE auto-locking front differential			
Driving Assistance	Electronic Hill Descent Control ECO / ECO Off / Work modes			
Power Steering	Dynamic Power Steering (DPS)			
SUSPENSIONS				
Front Suspension	Arched double A-arm / 11 in. (27.9 cm) travel			
F 101 1				

	EGO / EGO OII / Work inodes			
Power Steering	Dynamic Power Steering (DPS)			
SUSPENSIONS				
Front Suspension	Arched double A-arm / 11 in. (27.9 cm) travel			
Front Shocks	Twin tube gas charged shocks			
Rear Suspension	Arched TTA with external sway bar / 11 in. (27.9 cm) travel			
Rear Shocks	Twin tube gas charged shocks			
BRAKES				
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers			
Rear	Dual 220 mm ventilated disc brakes with hydraulic single-piston calipers			
Brake holding mechanism				

TIRES / WHEELS		
Front Tires	Maxxis† Bighorn 2.0† 27 x 9 x 14 in. (68.6 x 22.9 x 35.6 cm)	
Rear Tires	Maxxis Bighorn 2.0 27 x 11 x 14 in. (68.6 x 27.9 x 35.6 cm)	
Wheels	14-in. (35.6 cm) cast-aluminum	

DIMENSIONS /	CAPACITIES		
LxWxH	125.8 x 64 x 80 in. (319.5 x 162.5 x 203.2 cm)		
Wheelbase	83 in. (211.5 cm)		
Ground Clearance	13 in. (33 cm)		
Estimated Dry Weight	1,613.8 lb (732 kg)		
Cage	Profiled cage ROPS approved		
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)		
Cargo Box Capacity	1,000 lb (454 kg) California only: 600 lb (272.2 kg)		
Tailgate Load Capacity	250 lb (113.4 kg)		
Storage Capacity	Total: 16.2 gal (61.3 L) Under dash: 6 gal (22.8 L) Waterproof and removable box under passenger seat: 5.6 gal (21 L) Dash: 2 gal (7.7 L) Water-resistant and removable toolbox: 1.7 gal (6.3 L) Armrests and cup holders: 0.9 gal (3.5 L)		
Towing Capacity	2,500 lb (1134 kg)		
Payload Capacity	1,500 lb (680 kg)		
Fuel Capacity	10.6 gal (40 L)		
Person Capacity	3		

FEATURES			
Gauge	7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trip and hour meters,	Winch	4,500-lb (2,041 kg) winch with roller fairlead
	fuel, gear position, ECO / ECO Off / Work modes, seat belt, diagnostics, clock, battery voltage, engine temperature	Lighting	140 W lighting output from four 35-W reflectors ensuring a wide visiblity and LED tail lights
Battery	12 V (30 amp/h)	Seat	VERSA-PRO bench seat with bolster seats for additional lateral support, passenger seats flipping up, adjustable driver seat, underside hooks, reinforced seat skin and contoured bench to improve entrance/exit of the cab
Magneto	650 W		
Instrumentation	Lighter type DC outlets in the console (20-A) and two USB port in the dash storage	Protection	Heavy-duty front steel bumper, HMWPE full skid plate, aluminum rock sliders, full hard roof
		Hitch Type	2-in. hitch receiver
		Steering Wheel	Adjustable tilt steering

Factory 1-year limited warranty Extended Up to 30 months B.E.S.T. coverage





