§MAVERICK™ X3 MAX TURBO

HIGHLIGHTS

PLATFORM FEATURES

- 64-in. wide
- 135-in. wheelbase
- 13-in. of ground clearance
- High torque Dynamic Power Steering (DPS™)
- 20-in. suspension travel
- FOX† 2.5 PODIUM† QS3 Piggyback shocks
- 14-in. aluminum wheels
- 28-in. Maxxis† Bighorn 2.0† tires
- 4.5-in. digital display
- Rear tow hook

DEFIANT

Rear

T I IO A I

- Trademark Can-Am DNA with next generation design
- Low seating position
- Ergo-Lok cockpit with fourway adjustable seats

POWERFUL

- 120 hp turbocharged Rotax® ACE engine
- Advanced airflow dynamics
- QRS-X transmission

PRECISE

- TTX suspension with industry leading travel
- Ultra efficient and lightweight chassis
- Sharpest handling features

White / TUDBO

White / TURBO

Can-Am Red / TURBO

Hyper Silver & Can-Am Red / TURBO

7	D	EC	_/	W	ш	EE	C
ш	N	Eg		N'A'			F9

TIMES / WITE	LLO
Front Tires	Maxxis Bighorn 2.0 28 x 9 x 14 in. (71.1 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 28 x 11 x 14 in. (71.1 x 27.9 x 35.6 cm)
Wheels	14-in. (35.6 cm) cast-aluminum

ENGINE	TURBO
Туре	120 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled and high- perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high airflow L / H / N / R / P
Drive Train	Selectable 2WD / 4WD with Visco-Lok [‡] auto-locking front differential
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm with sway bar / 20-in. (50.8 cm) travel
Front Shocks	FOX 2.5 PODIUM Piggyback with QS3 compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar 20-in (50.8 cm) travel
Rear Shocks	FOX 2.5 PODIUM Piggyback with QS3 compression adjustment and bottom-out control
BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers

Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers

DIMENSIONS /	CAPACITIES
LxWxH	164 x 64 x 65.8 in.
	(416.6 x 162.5 x 167.1 cm)
Wheelbase	135 in. (342.9cm)
Ground Clearance	13 in. (33 cm)
Estimated Dry Weight	1,726 lb (782.9 kg)
Chassis / Cage	Dual-phase 980 steel
Rack Capacity	150 lb (68 kg) with
	LinQ™ quick-attach
Storage Capacity	Total: 3 gal (11.4 L)
	Glove box: 1.6 gal (6.2 L)
	Center console: 1.1 gal (4.1 L)
	Cup holders: 0.3 gal (1.1 L)
Fuel Capacity	10.5 gal (40 L)

FEATURES			
Gauge	4.5 in. (11.4 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trip and hour	Protection	Integrated front bumper, quarter-doors, HMWPE full skid plate, rear tow hook
	meters, fuel, gear position, SPORT / ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock,	Instrumentation	Lighter type DC outlet in central console
	auto shut off	Lighting	LED headlights and tail lights
Winch	N/A	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 30 months B.E.S.T. coverage





