## **≋OUTLANDER™ DPS™**

## HIGHLIGHTS

- Rotax® V-twin engine options
- New arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Torsional Trailing arm Independent (TTI) rear suspension
- Visco-Lok<sup>‡</sup> QE auto-locking front differential
- 14-in. cast-aluminum wheels
- 230-W lighting from headlights
- 625-W magneto

- High-strength, multifunction racks with LinQ<sup>™</sup> quick-attach accessory system
- 5.7-gal (21.4 L) water-resistant rear compartment
- RF Digitally Encoded Security System (D.E.S.S.™)
- Multifunction digital gauge



Orange / 650 / 850

ENGINES	650	850	
Туре	62 hp, Rotax 649.6 cc V-twin, liquid cooled	78 hp, Rotax 854 cc V-twin, liquid cooled	
Fuel Delivery System	Electronic Fuel Injection (EFI)	Intelligent Throttle Control (iTC™) with Electronic Fuel	
Transmission	CVT, P / R / N / H / L, standard engine braking		
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential		
Power Steering	Tri-Mode Dynamic Power Steering (DPS)		

SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel
Rear Shocks	Oil

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEELS		
Front Tires	ITP <sup>†</sup> Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)	
Rear Tires	ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)	
Wheels	14-in. cast-aluminum	

DIMENSIONS / CAPACITIES		
LxWxH	86 x 48 x 49.5 in. (218.4 x 121.9 x 126 cm)	
Wheelbase	51 in. (129.5 cm)	
Ground Clearance	11 in. (27.9 cm)	
Seat Height	34.5 in. (87.7 cm)	
Engine / Dry Weight*	650: 749 lb (341kg) 850: 800 lb (363 kg)	
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)	
Storage Capacity	Rear: 5.7 gal (21.4 L)	
Towing Capacity	1,650 lb (750 kg)	
Fuel Capacity	5.4 gal (20.5 L)	

<b>FEATURES</b>				
Gauge	Multifunction digital: Speedometer, tachometer (bar	4.5-in. digital display: Speedometer, tachometer,	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4	odometer, trip & hour meters,gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
	indicator, temperature and engine lights, fuel gauge, clock	electronic ruer gauge & clock	Seat	Standard
Winch	Prewired for available winch		Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.)
Protection	Mudguards			

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage



