©OUTLANDER™ X™ xc

HIGHLIGHTS

- Rotax® V-twin engine
- Intelligent Throttle Control (iTC™) with riding modes
- Front and rear FOX† 1.5 PODIUM† RC2 shocks
- 14-in. cast-aluminum beadlock wheels
- 26-in. ITP† Terracross radial tires
- Sport bumper with aluminum pre-runner
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- Front, center & footwell aluminum skid plates
- A-arms & TTI HMWPE protectors
- Aluminum taper-profile handlebar with full wrap handguards
- 625-W magneto

- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- 5.7-gal (21.4 L) water-resistant rear compartment
- · X package coloration



Rack Capacity

Storage Capacity

Towing Capacity

Fuel Capacity

ENGINE	1000R
Туре	91 hp, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok‡ QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel
Front Shocks	FOX 1.5 PODIUM RC2
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel
Rear Shocks	FOX 1.5 PODIUM RC2

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

Black, Hyper Silve	er & Can-Am Red / 1000R	
TIRES / WHEEL	S	
Front Tires	ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6cm)	
Rear Tires	ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)	
Wheels	14-in. cast-aluminum beadlock	
DIMENSIONS / CAPACITIES		
LxWxH	86 x 48 x 49.5 in.	
	(218.4 x 121,9 x 126 cm)	
Wheelbase	00 % 10 % 1010 IIII	
Wheelbase Ground Clearance	(218.4 x 121,9 x 126 cm)	
	(218.4 x 121,9 x 126 cm) 51 in. (129.5 cm)	

Front: 100 lb (45 kg) Rear: 200 lb (90 kg)

Rear: 5.7 gal (21.4 L)

1,650 lb (750 kg)

5.4 gal (20.5 L)

FEATURES			
Gauge	7.6-in wide digital display : Speedometer, tachometer, odometer, trips & hour meters, gear position, 4 x 4 indicator, temperature, engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Standard
Winch	Prewired for available winch	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Front bumper with pre-runner, aluminum taper-profile handlebar with full wrap handguards, front, center & footwell aluminum skid plates, A-arms		

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage



and TTI HMWPE protectors, mudguards