

can-am. **OUTLANDER MAX 6X6 XU+ 1000 T**

1000

Туре	80HP, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 4WD / 6WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed Category	Up to 60 km/h
SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3cm) travel
Front Shocks	Oil
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25,1 cm) travel
Rear Shocks	Oil
TIRES / WHEELS	**
	Oil Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
TIRES / WHEELS	Carlisle† ACT HD 26 x 8 x 12 in.
TIRES / WHEELS Front Tires	Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm) Carlisle† ACT HD 26 x 10 x 12 in.
TIRES / WHEELS Front Tires Rear Tires	Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm) Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
TIRES / WHEELS Front Tires Rear Tires Wheels	Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm) Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
TIRES / WHEELS Front Tires Rear Tires Wheels BRAKES	Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm) Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm) 12-in. cast-aluminum Dual 214 mm ventilated disc brakes with
TIRES / WHEELS Front Tires Rear Tires Wheels BRAKES Front	Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm) Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm) 12-in. cast-aluminum Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers Dual 214 mm ventilated disc brakes with
TIRES / WHEELS Front Tires Rear Tires Wheels BRAKES Front Rear	Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm) Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm) 12-in. cast-aluminum Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers Dual 214 mm ventilated disc brakes with

ENGINE

Wheelbase

Seat Height

Rack Capacity

Storage Capacity

Towing Capacity

Fuel Capacity

Ground Clearance



CEAT	URES
FEAL	ひれたる

FEATURES	
Gauge	4.5-in. digital display: Speedometer, tachometer, odometer, trip & hour meters,gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock
Instrumentation	Lighter type DC Outlet in console, standard connector in the back (15-A)
Anti-theft System	Digitally Encoded Security System (D.E.S.S. $^{\text{TM}}$)
Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Winch	3,500-lb (1,588 kg) winch
T-Category features	Towing hitch with trailer plug, directionnal indicators, position lamps, mirrors, horn
Seat	Reinforced seat skin Convertible Rack System (CRS)
Protection	Heavy-Duty front bumper, Central skid plate, heated grips
WARRANTY	
Factory warranty	2-years BRP limited warranty



228,5cm

27,9 cm

87,7 cm

Front: 45 kg / Rear: 318 kg

Dual-level cargo box with sidewalls and tailgate Rear: 18,5 gal (70 L)

907 Kg trailer with brakes 674 Kg trailer without brakes

20,5 L

