

CON-OM. MAVERICK TRAIL 800 T

HIGHLIGHTS

AGILE • Sturdy engine and transmission

• Easy Handling and capabilities

· Front and rear suspension designed for trail riding

ADVENTUROUS

• Meaningful functionalities and versatilities

• Enhanced comfort with Ergo-Lok cockpit

· Build your Maverick Trail that fits your needs

• Can-Am design and proven fit & finish
• Enhanced protection

More adventure and less maintenance

PLATFORM FEATURES

TIRES / WHEELS

• 50 in. wide (52 in. with mirrors)

• 90.6 in. wheelbase

• 10 in. of ground clearance

• Up to 10.5 in. suspension travel

• 7.6 in. (19.3 cm) wide digital display with keypad

• SPORT / ECO™ modes

Ergoprint seats

Net (instead of doors)

• RF key DESS with Start / Stop button

Mudguard and Mudflap

Rear hitch and tow ball

• 7-pin trailer connexion (12V)

LED tail lights with halo glow effect

 Horn, flashers and position lamps, left/right mirrors, license plate support, hook on front metal bumper, driver

seat detector, Low brake fluid sensor



ENGINES	800
Туре	51 hp, Rotax® 799.9 cc, V-twin, liquid cooled, with catalytic converter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable 2WD / 4WD with Visco-Lok† auto- locking front differential
Driving Assistance	Electronic Hill Descent Control SPORT / ECO™ modes
Power Steering	N/A

SUSPENSIONS	
Front Suspension	Double A-arm with sway bar / 10 in. (25.4 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	TTA with sway bar / 10.5 in. (26.7 cm) travel
Rear Shocks	Twin tube gas charged shocks

Front Tires	Carlisle ACT 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle ACT 26 x 9 x 12 in. (66 x 22.9 x 30.5 cm)
Wheels	12 in. (30.5 cm) steel

BRAKES	
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers

DIMENSIONS / CAPACITIES

Estimated Dry Weight	1,314 lb (596 kg)
Chassis / Cage	Profiled cage ROPS approved
LxWxH	118 x 52 x 69 in. (300,5 x 132 x 175,5 cm)
Wheelbase	90.6 in. (230.1 cm)
Ground Clearance	10 in. (25.4 cm)
Cargo Box Capacity	300 lb (136 kg)
Towing Capacity	1,500 lb (680 kg)
Storage Capacity	Total: 5.3 gal (20.2 L) Glove Box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and Cup holders: 0.8 gal (3.1 L)
Fuel Capacity	10 gal (38 L)

	Center console and Cup holders: 0.8 gal (3.1 L)
Fuel Capacity	10 gal (38 L)
FEATURES	
Gauge	7.6 in. (19.3 cm) wide digital display with keypad Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature
Instrumentation	Lighter type DC outlet in console (20-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button
Magneto	650-W
Lighting	Two 55 W reflectors and LED tail lights
Winch	N/A
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper Full skid plate Mudguard and Mudflap
Hitch Type	2 in. Rear hitch receiver and tow ball

WARRANTY

Factory warranty 2-years BRP limited warranty



