

Can-am. MAVERICK TRAIL DPS 800 / 1000 T

HIGHLIGHTS	800	1000	
AGILE	Sturdy engine and transmission Easy Handling and capabilities Front and rear suspension designed for trail riding		
ADVENTUROUS	Meaningful functionalities and versatilities Enhanced comfort with Ergo-Lok cockpit Build your Maverick Trail that fits your needs		
CONFIDENT	 Can-Am design and proven fit & finish Enhanced protection More adventure and less maintenance 		
PLATFORM FEATURES	• 50 in. wide (52 in. with mirrors) • 90.6 in. Wheelbase • 10 in. of ground clearance • Up to 10.5 in. suspension travel • 7.6 in. (19.3 cm) wide digital display with keypad • SPORT / ECO™ modes • Net (instead of doors) • RF key DESS with Start / Stop button • Mudguard and Mudflap • Rear hitch and tow ball • 7-pin trailer connexion (12V) • LED tail lights with halo glow effect • Horn, flashers and position lamps, left/right mirrors, license plate support, hook on front metal bumper, driver seat detector, Low brake fluid sensor		
SPECIFIC TO DPS T PACKAGE	Dynamic Power Steering (DPS™) 12 in. (30.5 cm) aluminum wheels Ergoprint seats with color accents over 60KM/H top speed Open front diff. with Brake Traction Control (BTC) Dynamic Brake Control (ABS + HHC + HDC) Dynamic Traction Control (BTC + DTC) Dynamic Traction Control (TCS can be switched off)		

Туре	51 hp, Rotax® 799.9 cc, V-twin, liquid cooled, with catalytic converter	75 hp, Rotax® 976 cc, V-twin, liquid cooled, with catalytic converter	
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		
Transmission	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P		
Drive Train	Selectable 2WD / 4WD with Open front diff. with Brake Traction Control (BTC)		
Driving Assistance	Electronic Hill Descent Control SPORT / ECO™ modes		
Power Steering	Dynamic Power Steering (DPS)		
SUSPENSIONS			
Front Suspension	Double A-arm with sway bar / 10 in. (25.4 cm) travel		
Front Shocks	Twin tube gas charged shocks		
Rear Suspension	TTA with sway bar / 10.5 in. (26.7 cm) travel		
Rear Shocks	Twin tube gas o	charged shocks	
TIRES / WHEELS			
Front Tires	Carlisle ACT 26 x 8 x 12	Carlisle ACT 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)	
Rear Tires	Carlisle ACT 26 x 9 x 12 in. (66 x 22.9 x 30.5 cm)		
Wheels	12 in. (30.5 cm) cast-aluminum		

800

ENGINES



BRAKES	800	1000
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers with Dynamic Brake Control (ABS + HHC + HDC)	
Rear	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers with Dynamic Brake Control (ABS + HHC + HDC)	
DIMENSIONS / CAPACITIES		
Estimated Dry Weight	1,331 lb (603.7 kg)	1,364 lb (618.7 kg)
Chassis / Cage	Profiled cage ROPS approved	
LxWxH	118 x 52 x 69 in. (300,5 x 132 x 175,5 cm)	
Wheelbase	90.6 in. (230.1 cm)	
Ground Clearance	10 in. (2	25.4 cm)
Cargo Box Capacity	300 lb (136 kg)
Towing Capacity	1,500 lb (680 kg)	
Storage Capacity	Glove Box: 4. Driver storage	gal (20.2 L) .1 gal (15.6 L) : 0.4 gal (1.5 L) p holders: 0.8 gal (3.1 L)
Fuel Capacity	10 gal (38 L)	
FEATURES		
Gauge	key Speedometer, tachor and hour meters, fuel, ECO™ mode, seat belt and rear diff lock indica	e digital display with pad meter, odometer, trips gear position, SPORT / and 4 x 4 indicator, front tors, diagnostics, clock, naine temperature

	Speedometer, tachometer, odometer, trips
	and hour meters, fuel, gear position, SPORT /
	ECO™ mode, seat belt and 4 x 4 indicator, front
	and rear diff lock indicators, diagnostics, clock,
	battery voltage, engine temperature
Instrumentation	Lighter type DC outlet in console (20-A)
Anti-theft System	RF Digitally Encoded Security System
	(D.E.S.S. [™]) with Start/ Stop button
Magneto	650-W
Lighting	Two 55 W reflectors and LED tail lights
Winch	N/A
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper
	Full skid plate
	Mudguard and Mudflap
Hitch Type	2 in. Rear hitch receiver and tow ball

©2020 Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. "Base model dry weight shown. "Visco-Lok is a trademark of GKN Viscodrive GmbH. 'All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Ride responsibly. BRP high recommends that all ATV drivers take a training ourse. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

WARRANTY

Factory warranty

1000



2-years BRP limited warranty