MY24 OUTLANDER MAX DPS 1000R



Legion Red

ENGINE

BRAKES

Front

Rear

| Туре | 68 k W (91 hp), Rotax® 976 cc V-twin, liquid cooled |
|---|--|
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI) |
| Transmission | CVT L / H / N / R / P |
| Drive Train | Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential |
| Driving Assistance | Work / Standard / Sport modes Intelligent Engine Braking (iEB™) |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) |
| Cread Category | Over 60 km/h |
| Speed Category | |
| Speed Category SUSPENSIONS Front Suspension | Arched double A-arm with front sway bar |
| SUSPENSIONS | |
| SUSPENSIONS | Arched double A-arm with front sway bar |
| SUSPENSIONS Front Suspension | Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel |
| SUSPENSIONS Front Suspension Front Shocks | Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel Twin tube Torsional Trailing arm Independent (TTI) |
| SUSPENSIONS Front Suspension Front Shocks Rear Suspension | Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel Twin tube Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel |
| SUSPENSIONS Front Suspension Front Shocks Rear Suspension Rear Shocks | Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel Twin tube Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel |

Dual 214 mm disc brakes with hydraulic

Single 214 mm disc brake with hydraulic

twin-piston calipers

twin-piston caliper

HIGHLIGHTS

- Tri-Mode Dynamic Power Steering (DPS)
- Visco-Lok† QE auto-locking front differential
- 14 in. (35.6 cm) cast-aluminum wheels • 26 in. (66 cm) ITP Terracross radial tires
- Heavy-duty front bumper
- Passenger seat
- · Extended wheelbase
- Raised floorboards

| DIMENSIONS / CAPACITIES | |
|-------------------------|---|
| Estimated Dry Weight * | 884 lb (401 kg) |
| L x W x H | 94 x 48 x 53 in. (238.8 x 121.9 x 135 cm) |
| Wheelbase | 59 in. (149.9 cm) |
| Ground Clearance | 11 in. (27.9 cm) |
| Seat Height | 34.5 in. (87.7 cm) |
| Rack Capacity | Front: 100 lb (45 kg) / Rear: 200 lb (90 kg) |
| Storage Capacity | Rear: 5.7 gal (21.4 L) |
| Towing Capacity | 1,650 lb (750 kg) |
| Fuel Capacity | 5.4 gal (20.5 L) |

FEATURES

| Gauge | 4.5 in. digital display |
|-------------------|---|
| Instrumentation | DC outlet, 15-A connector |
| Anti-theft System | RF Digitally Encoded Security System (D.E.S.S.™) |
| Lighting | LED headlights |
| Winch | Prewired for available winch |
| Seat | Convertible Rack System (CRS) |
| Handlebar | Standard |
| Protection | Heavy-duty front bumper Mudguards |
| | |

WARRANTY

Factory warranty

2-year BRP limited warranty









©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, * and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †All trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety: the particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by the age of 16 and older. Never carry passengers on any ATV not specifically designated for such use. Some models depicted may include optional equipment.