MY24 RENEGADE X MR 1000R



HIGHLIGHTS

- Rotax® snorkeled V-Twin engine with relocated CVT intake and outlet
- Continuously Variable Transmission (CVT) with Extra Low L-Gear • Tri-Mode Dynamic Power Steering (DPS)
- Visco-4Lok front differential FOX† 1.5 PODIUM† QS3 shocks
- 14 in. (35.6 cm) cast-aluminum beadlock wheels
- 30 in. (76.6 cm) ITP Cryptid† tires
- 3,500-lb (1,588 kg) winch
- Front & central aluminum skid plate
- · Heavy-duty front and rear bumpers
- · Aluminum taper-profile handlebar with grab handle and full-wrap handguards
- X-package coloration, graphics and seat cover

| ENGINE | 1000R |
|----------------------|--|
| Туре | 68 k W (91 hp), Rotax® 976 cc V-twin, |
| | snorkeled, liquid cooled |
| Fuel Delivery System | Intelligent Throttle Control (iTC™) |
| | with Electronic Fuel Injection (EFI) |
| Transmission | CVT |
| | Extra low L / H / N / R / P |
| Drive Train | Selectable 2WD / 4WD / Lock 4WD |
| | with Visco-4Lok front differential |
| Driving Assistance | Work / Standard / Sport modes |
| | Intelligent Engine Braking (iEB™) |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) |
| | |
| SUSPENSIONS | |
| Front Suspension | Arched double A-arm with front sway bar |
| Front Shocks | FOX† 1.5 PODIUM† QS3 |
| Rear Suspension | Torsional Trailing arm Independent (TTI) |
| Rear Shocks | FOX† 1.5 PODIUM† QS3 |
| | |
| TIRES / WHEELS | |
| Front & Rear Tires | ITP† Cryptid 30 x 9/9 x 14 in. |
| | (76.6 x 22.9 / 22.9 x 35.6 cm) |
| Wheels | 14 in. (35.6 cm) cast-aluminum beadlock |
| | |
| BRAKES | |
| Front | Dual 214 mm disc brakes with hydraulic |
| | |

twin-piston calipers

twin-piston caliper

Single 214 mm disc brake with hydraulic

DIMENSIONS / CAPACITIES

| Estimated Dry Weight * | 971 lb (440 kg) |
|------------------------|---------------------------------------|
| L×W×H | 83 x 50 x 56 in. (224 x 127 x 131 cm) |
| Wheelbase | 51 in. (129.5 cm) |
| Ground Clearance | 12.5 in. (31.8 cm) |
| Seat Height | 36.75 in. (93.3 cm) |
| Rack Capacity | Rear: 35 lb (16 kg) |
| Storage Capacity | N/A |
| Towing Capacity | 1,300 lb (590 kg) |
| Fuel Capacity | 5.4 gal (20.5 L) |

FEATURES

| TEATOREO | |
|-----------------|---|
| Gauge | 4.5 in. digital display |
| Instrumentation | DC outlet, 15-A connector |
| Ingnition | RF Digitally Encoded Security System (D.E.S.S.™) with cord |
| Lighting | LED headlights |
| Winch | 3,500-lb (1,588 kg) winch |
| Seat | Standard |
| Handlebar | Aluminum taper-profile handlebar with grab handle and full wrap handguards |
| Protection | Front & rear bumpers Mudguards Front & central aluminum skid plate |

WARRANTY & EXTENDED SERVICE

| Factory warranty | 2-year BRP limited warranty |
|------------------|-----------------------------|
|------------------|-----------------------------|



Rear





REQUEST A QUOTE



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, * and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †All trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety: the particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by the age of 16 and older. Never carry passengers on any ATV not specifically designated for such use. Some models depicted may include optional equipment.