

2026 TRAXTER XU HD11 T ABS



PACKAGE HIGHLIGHTS

- Open-4Lok front differential with ABS system
- Dynamic Power Steering (DPS)
- Brake holding mechanism
- 65 in wide with Arched Double A-Arm and sway bar
- 4,500 lb (2,041 kg) winch with synthetic cable
- Full heavy-duty HMW plastic skid plate
- LED headlights and LED tail lights with back up light
- Full heater
- Flashers
- Left and right sides EC approved mirrors
- Horn with turning signal lever
- Seat sensor
- Speed limiter: 30 - 100 km/h
- ABS system

| ENGINES | HD11 |
|----------------------|--|
| Type | 95 hp / 95 Nm Rotax® ACE (Advanced Combustion Efficiency) 999 cc triple cylinder, liquid cooled |
| Fuel Delivery System | Intelligent Throttle Control (iTCTM) with Electronic Fuel Injection (EFI) |
| Transmission | pDrive primary and Quick Response System X (QRS-X) CVT with high airflow and Electronic Drive Belt Protection L / H / N / R / P |
| Drive Train | Selectable Turf Mode / 2WD / 4WD with Open-4Lok front differential with ABS system |
| Driving Assistance | CVT Engine Braking Sport / Normal / Work modes Speed Limiter |
| Power Steering | Dynamic Power Steering (DPS) |

| SUSPENSIONS | |
|------------------|--|
| Front Suspension | Arched Double A-Arm with sway bar / 12 in. (30.5 cm) suspension travel |
| Front Shocks | Twin tube gas charged shocks |
| Rear Suspension | Arched Double A-Arm / 12 in. (30.5 cm) suspension travel |
| Rear Shocks | Twin tube gas charged shocks |

| TIRES / WHEELS | |
|--------------------|-------------------------------------|
| Front / Rear Tires | XPS Trail King 2 29 x 9/11 x 14 in. |
| Wheels | 14 in. cast-aluminum |

| BRAKES | |
|--------|--|
| Front | Dual 262 mm disc brakes with hydraulic twin-piston calipers (32 mm) |
| Rear | Dual 236 mm disc brakes with hydraulic single piston caliper (32 mm) |
| Other | Brake holding mechanism |

| DIMENSIONS / CAPACITIES | |
|-------------------------|--|
| Cage | Profiled cage. ROPS approved |
| Estimated Dry Weight* | 1,850 lb (839 kg) |
| L x W x H | 122.7 x 65 x 81 in. (312 x 165 x 206 cm) |
| Wheelbase | 85 in. (216 cm) |
| Ground Clearance | 14 in. (35.6 cm) |
| Cargo Box Dimensions | 38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm) |
| Cargo Box Capacity | 1,000 lb (454 kg) |
| Tailgate Load Capacity | 250 lb (113.4 kg) |
| Storage Capacity | Weather resistant above gage glove box Weather resistant passenger glove box with USB-C, USB-A & DC outlet Cubby storage and lower dash storage 3.7 gal (14 L) under seat removable bin |
| Towing Capacity | 2,450 lb (1,111 kg) |
| Payload Capacity | 1,500 lb (680 kg) |
| Fuel Capacity | 11.9 gal (45 L) |
| Person Capacity | 3 |

| FEATURES | |
|-------------------|--|
| Gauge | 4.5 in. wide digital display with keypad |
| Battery | 400 CCA (30 amp/h) |
| Magneto | 650-W |
| Instrumentation | USB outlet Lighter DC Outlet |
| Anti-theft System | RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button |
| Lighting | LED headlights LED tail lights with flashers LED signature |
| Winch | 4,500 lb (2,041 kg) winch with synthetic cable |
| Seat | Adjustable driver seat 60/40 Reinforced |
| Steering Wheel | Premium steering wheel with keypad space Tilt steering adjustment |
| Protection | Full heavy-duty HMW plastic skid plate Door safety net Lower front mudflap |
| Hitch Type | 2 in. hitch receiver with rear hitch, tow ball and trailer connexion |

| WARRANTY & EXTENDED SERVICE | |
|-----------------------------|-----------------------------|
| Factory warranty | 2-year BRP limited warranty |



REQUEST A QUOTE



©2025 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrives GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.