



can-am.

DEFENDER

2020 Can-Am DEFENDER HD8

2020 Polaris[†] Ranger 1000

| | | | |
|------------------------------|---|--|--|
| Engine | | 799.9cc Rotax® V-twin, liquid cooled, EFI | 999cc twin cylinders, liquid cooled, EFI |
| Transmission | ✓ | PRO-TORQ transmission with Quick Response System, high airflow ventilation and Electronic Drive Belt Protection | CVT |
| Traction System | | Selectable Turf Mode / 2WD / 4WD with Visco-Lok [†] QE auto-locking front differential | High performance True On-Demand AWD / 2WD / VersaTrac Turf Mode |
| Driving Assistance | ✓ | Electronic Hill Descent Control and ECO / ECO Off / Work driving modes | Not available |
| Suspensions | ✓ | FR : Double A-arm / 10 in. RR : Torsional Trailing Arm (TTA) with external sway bar / 10 in. | FR : Double A-arm / 10 in. RR : Double A-arm / 10 in. |
| Wheels & Tires | ✓ | 12 in. steel wheels with 27 in. Maxxis Bighorn [†] 2.0 tires | 12-in. steel wheels with 25 in. 489 tires |
| Wheelbase | ✓ | 83 in. | 81 in. |
| Ground clearance | | 11 in. | 12 in. |
| Fuel capacity | | 10.6 gal (40 L) | 11.35 gal (43 L) |
| Hitch Type & Towing Capacity | ✓ | 2 in. hitch receiver with 2,500 lb (1134 kg) of towing capacity | 2 in. hitch receiver with 2500 lb (1134 kg) of towing capacity |
| Payload Capacity | | 1,500 lb (680 kg) | 1,500 lb (680 kg) |
| Cargo Box Versatility | ✓ | 4 x steel anchors / tie-down points, 4 x 5-gallon (18.9 L) pail recesses, 14 x LinQ quick-attach, 1 x 3 and plywood separators and bed extender-ready, Sturdy removable tailgate allowing for 250 lb capacity, 4 integrated cup recesses and a ruler in tailgate | Lock & Ride system |
| Seat | ✓ | VERSA-PRO bench seat with passenger seats flipping up, underside hooks and contoured bench to improve entrance/exit of the cab | Standard bench seat |
| Storage | | Under dash, dash, armrests and cup holders 3.1 gal / 11.7 L (Storage accessories available) | Fixed glovebox, 6 cup holder and 2 bottle holders, under-seat storage 18.6 gal / 70.4 L |
| Gauge | ✓ | 4.5 in. Digital display | 4 in. LCD information center |
| Lighting | ✓ | 140 W lighting output from four 35-W reflectors ensuring a wide visibility and LED tail lights | 55-W low / 60-W high, LED Tail lights |