©OUTLANDER™ MAX 6x6 XT™ 1000

HIGHLIGHTS

- Rotax® V-twin engine
- New arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with Extra-Low L Gear
- 700-lb (318 kg) capacity Dual-Level[™] cargo box with modular accessories
- 3,000-lb (1,361 kg) WARN† winch with roller fairlead
- 1,650-lb (750 kg) towing capacity
- Tri-Mode Dynamic Power Steering (DPS)
- Double Torsional Trailing arm Independent (TTI2) rear suspension

- 12-in. cast-aluminum wheels
- Relocated air intakes
- · Quick release rear sway bar
- High-strength, multifunction racks with LinQ[™] quick-attach accessory system
- RF Digitally Encoded Security System (D.E.S.S.™)



Pure Magnesium Metallic / 1000

ENGINE	1000
Туре	82 hp, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra-Low L, standard engine braking
Drive Train	Selectable 4WD / 6WD with Visco-Lok [‡] QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel
Front Shocks	Oil
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25.1 cm) travel
Rear Shocks	Oil

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHEELS			
Front Tires	Carlisle [†] ACT radial 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)		
Rear Tires	Carlisle ACT radial 26 x 10 x 12 in (66 x 25.4 x 30.5 cm)		
Wheels	12-in. cast-aluminum		

DIMENSIONS / CAPACITIES		
LxWxH	124.8 x 48.5 x 55.3 in. (317 x 123 x 140 cm)	
Wheelbase	90 in. (228.5cm)	
Ground Clearance	11 in. (27.9 cm)	
Seat Height	34.5 in. (87.7 cm)	
Dry Weight*	1170 lb (531 kg)	
Rack Capacity	Front: 100 lb (45 kg) Rear: 700 lb (318 kg)	
Storage Capacity	Dual-level cargo box with sidewalls and tailgate Rear: 18.5 gal (70 L)	
Towing Capacity	1,650 lb (750 kg)	
Fuel Capacity	5.4 gal (20.5 L)	

FEATURES			
Gauge	Multifunction digital: Speedometer, tachometer (bar graph RPM, bottom	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
	gauge, clock	Seat	Convertible Rack System (CRS)
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.)
Protection	Heavy-duty front bumper, handlebar wind deflectors, central skid plate		

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage



