

2020 OUTLANDER™ MAX DPS™ 450 / 570

HIGHLIGHTS

- Rotax® engine options
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- Double A-arm front suspension
- Torsional Trailing arm Independent (TTI) rear suspension
- 5.4-gal (20.5 L) fuel capacity
- 1,300-lb (590 kg) towing capacity
- Surrounding Spar Technology (SST) G2L frame with Geometric Contact Control
- 500-W magneto
- Steel racks with LinQ™ quick-attach accessory system and a combined 360 pounds (163.3 kg) capacity
- 2.9-gal (10.9 L) water-resistant rear compartment
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- Raised floorboards



Orange / 450 / 570
Green / 450 / 570

ENGINES	450	570
Type	38 hp, Rotax 427 cc single cylinder, liquid cooled	48 hp, Rotax 570 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)	
Transmission	CVT, P / R / N / H / L, standard engine braking	
Drive Train	Selectable 2WD / 4WD with Visco-Lok® QE auto-locking front differential	
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	

TIRES / WHEELS	
Front Tires	Carlisle® Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	Carlisle Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12-in. steel

SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel
Rear Shocks	Oil

DIMENSIONS / CAPACITIES	
L x W x H	91 x 46 x 52.5 in. (231 x 116.8 x 133 cm)
Wheelbase	59 in. (149.9 cm)
Ground Clearance	10.5 in. (26.7 cm)
Seat Height	33.8 in. (85.8 cm)
Engine / Dry Weight*	450 / 715 lb (324 kg) 570 / 741 lb (336 kg)
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)
Storage Capacity	Rear: 2.9 gal (10.9 L)
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

FEATURES			
Gauge	Multifunction digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for available winch	Lighting	70 W from dual 35-W front light / brake light
Protection	N/A	Seat	Convertible Rack System (CRS)
		Anti-theft System	N/A

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage

BEST PROTECTION ©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN ViscoDrive GmbH. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

can-am.

Can-AmOffroad.com

