SOUTLANDER DPS 450 / 570

HIGHLIGHTS

- Rotax[®] engine options
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- Double A-arm front suspension • Torsional Trailing arm Independent (TTI)
- rear suspension
- Visco-Lok[‡] QE auto-locking front differential •
- 5.4-gal (20.5 L) fuel capacity
- 1,300-lb (590 kg) towing capacity
- Surrounding Spar Technology (SST) G2 frame • with Geometric Contact Control
- 500-W magneto •
- Multifunction digital gauge

- Steel racks with LinQ[™] quick-attach accessory system and a combined 360 pounds (163.3 kg) capacity • 2.9-gal (10.9 L) water-resistant
- rear compartment



Orange / 450 / 570 Green / 450 / 570 🕷 Mossy Oak† Break-Up Country Camo† / 450 / 570

450	570	
38 hp, Rotax 427 cc single cylinder, liquid cooled	48 hp, Rotax 570 cc V-twin, liquid cooled	
Electronic Fuel Injection (EFI)		
CVT, P / R / N / H / L, standard engine braking		
Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential Tri-Mode Dynamic Power Steering (DPS)		

SUSPENSIONS			
Front Suspension	Double A-arm 9 in. (22.9 cm) travel		
Front Shocks	Oil		
Rear Suspension	Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel		
Rear Shocks	Oil		
BRAKES			
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers		
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper		

Carlisle [†] Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Carlisle Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
12-in. steel

DIMENSIONS / CAPACITIES				
LxWxH	83 x 46 x 49 in. (211 x 116.8 x 124 cm)			
Wheelbase	51 in. (129.5 cm)			
Ground Clearance	10.5 in. (26.7 cm)			
Seat Height	33.8 in. (85.8 cm)			
Engine / Dry Weight*	450 / 678 lb (308 kg) 570 / 704 lb (319 kg)			
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)			
Storage Capacity	Rear: 2.9 gal (10.9 L)			
Towing Capacity	1,300 lb (590 kg)			
Fuel Capacity	5.4 gal (20.5 L)			

FEATURES Gauge	Multifunction digital: Speedometer, tachometer, odometer,	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Lighting	70 W from dual 35-W front light / brake light
Winch	Prewired for available winch	Seat	Standard
Protection	N/A	Anti-theft System	N/A
WARRANTY			
Factory	6-months limited warranty		
Extended	Up to 36 months B.E.S.T. coverage		

©2019 Bombardier Recreational Products Inc (BRP). All rights reserved. TM, [©] and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. ⁺Base model dy weight shown. ⁴Visco-Lok is a trademark of GKN Viscodrive GmbH. ¹All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly, BRP high recommends that all AV drivers take a training course. For addy and training information, as your caled or not IL OSA and the XIV Sately Institute at 11 (800) 887-2887. In Canada, call the Canadian Sately Council at 11 (613) 739-1535 et 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. AIVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any AIV not specifically designated for such use.





Can-AmOffroad.com