©OUTLANDER™ MOSSY OAK® EDITION 450 / 570

HIGHLIGHTS

- Rotax[®] engine options
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 3,000-lb (1,361 kg) WARN[†] winch with roller fairlead
- 12-in. cast-aluminum wheels
- 26-in. Carlisle[†] ACT HD 6-ply tires
- · Heavy-duty front and rear bumpers
- Aluminum A-arm protectors
- Front, center & footwell skid plates

- · Heated grips and throttle
- Wind deflectors
- Torsional Trailing arm Independent (TTI) rear suspension
- Steel racks with LinQ[™] quick-attach accessory system and a combined 360 pounds (163.3 kg) capacity



Mossy Oak Break-Up Country Camo† / 450 / 570

ENGINES	450	570	
Туре	38 hp, Rotax 427 cc single cylinder, liquid cooled	48 hp, Rotax 570 cc V-twin, liquid cooled	
Fuel Delivery System	Electronic Fuel Injection (EFI)		
Transmission	CVT, P / R / N / H / L, standard engine braking		
Drive Train	Selectable 2WD / 4WD with Visco-Lok [‡] QE auto-locking front differential		
Power Steering	Tri-Mode Dynamic Power Steering (DPS)		

SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel
Rear Shocks	Oil

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEE	LS
Front Tires	Carlisle ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS / C/	DACITIES
DIMENSIONS / CA	83 x 46 x 49 in. (211 x 116.8 x 124 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	11.5 in. (29.2 cm)
Seat Height	33.8 in. (85.8 cm)
Engine / Dry Weight*	450: 678 lb (308 kg) 570: 708 lb (319kg)
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)
Storage Capacity	Rear: 2.9 gal (10.9 L)
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES			
Gauge	Multifunction digital: Speedometer, tachometer, odometer,	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Lighting	70 W from dual 35-W front light / brake light
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Seat	Reinforced Seat Skin
Protection	Heavy-duty front & rear bumpers, front, central & footwell aluminum skid plates, aluminum a-arms protectors, heated grips & throttle, handlebar wind deflectors	Anti-theft System	N/A

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage

©2019 Bombardier Recreational Products Inc (BRP). All rights reserved. TM, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP USInc. *Base model dry weight shown. *Visco-Lok is a trademark of GRN its Codrive GmbH. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovantia. BRP reserves the right at anythine to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly, BRP highly recommends that all AIV drivers take a training course. For after your safety and training information, see puur dealer or, in U.S.A. call the AIV Safety Institute at 1 (801 a87-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1355 set 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that ridding and alcohol /drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving, Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any AIV not specifically designated for such use.

