

# 2020 OUTLANDER™ MOSSY OAK<sup>†</sup> EDITION 650

## HIGHLIGHTS

- Rotax® V-twin engine
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 3,000-lb (1,361 kg) WARN<sup>†</sup> winch with roller fairlead
- 12-in. cast-aluminum wheels
- 26-in. Carlisle<sup>†</sup> ACT HD 6-ply tires
- Heavy-duty front and rear bumpers
- Heated grips and throttle
- A-arms & TTI HMWPE protectors
- Torsional Trailing arm Independent (TTI) rear suspension
- Handlebar wind deflectors
- Wind deflectors
- Front, central & footwell aluminum skid plates
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- RF Digitally Encoded Security System (D.E.S.S.™)
- 5.7-gal (21.4 L) water-resistant rear compartment



 Mossy Oak Break-Up Country Camo<sup>†</sup> / 650

ENGINE	650
Type	62 hp, Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok <sup>‡</sup> QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

TIRES / WHEELS	
Front Tires	Carlisle ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum


SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel
Rear Shocks	Oil

DIMENSIONS / CAPACITIES	
L x W x H	86 x 48 x 49.5 in. (218.4 x 121.9 x 126 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	12 in. (30.5 cm)
Seat Height	34.5 in. (87.7 cm)
Dry Weight*	749 lb (341 kg)
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,650 lb (750 kg)
Fuel Capacity	5.4 gal (20.5 L)

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

FEATURES			
Gauge	Multifunction digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Protection	Heavy-duty front & rear bumpers, front, central & footwell aluminum skid plates, A-arms and TTI HMWPE protectors, heated grips & throttle, handlebar wind deflectors, mudguards	Seat	Standard
		Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.)

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage

 ©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. <sup>™</sup>, <sup>®</sup> and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. \*Base model dry weight shown. <sup>‡</sup>Visco-Lok is a trademark of GKN Viscodrive GmbH. <sup>†</sup>All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.



Can-AmOffroad.com

