

# 2020 RENEGADE® X™ mr 570

## HIGHLIGHTS

- Rotax® snorkeled V-Twin engine with relocated CVT intake and outlet
- 28-in. ITP® Mega Mayhem tires
- 12-in. cast-aluminum beadlock wheels
- Front and rear FOX† 1.5 PODIUM‡ shocks
- Tri-Mode Dynamic Power Steering (DPS™)
- Front & central aluminum skid plates
- Torsional Trailing arm Independent (TTI) rear suspension
- Heavy-duty front and rear bumpers
- Aluminum taper-profile handlebar with grab handle, full wrap handguards
- Continuously Variable Transmission (CVT) with engine braking
- Mudguards
- Multifunction digital gauge
- X-package coloration, graphics and seat cover



Black, Gray & Sunburst Yellow / 570

## ENGINE

### 570

Type	48 hp, Rotax 570 cc V-twin, snorkeled, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok® QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

## TIRES / WHEELS

Front Tires	ITP Mega Mayhem 28 x 8 x 12 in. (71.1 x 20.3 x 30.5 cm)
Rear Tires	ITP Mega Mayhem 28 x 10 x 12 in. (71.1 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum beadlock

## SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar
Front Shocks	FOX 1.5 PODIUM
Rear Suspension	Torsional Trailing arm Independent (TTI)
Rear Shocks	FOX 1.5 PODIUM

## DIMENSIONS / CAPACITIES

L x W x H	83 x 50 x 56 in. (224 x 127 x 131 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	12 in. (30.5 cm)
Seat Height	35.25 in. (89.5 cm)
Dry Weight*	865 lb (393 kg)
Rack Capacity	Rear: 35 lb (16 kg)
Storage Capacity	N/A
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

## BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

## FEATURES

Gauge	Multifunction digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for available winch	Lighting	240 W from 4 fender mounted projector beam headlamps (60 W) with tail light / brake light
Protection	Front & rear bumpers, aluminum taper-profile handlebar with grab handle, full wrap handguards, mudguards, front & central aluminum skid plate	Seat	Standard
		Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)

## WARRANTY

Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage



©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. \*Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

**can-am.**

Can-AmOffroad.com

