

2020 COMMANDER™

HIGHLIGHTS

- Double A-arm front suspension with sway bar
- Torsional Trailing arm Independent (TTI) rear suspension with external sway bar
- Visco-Lok[‡] auto-locking front differential
- Intelligent Throttle Control (iTC™)
- Industry's exclusive Dual-Level™ cargo box
- 27-in. Maxxis Bighorn 2.0[†] tires
- Adjustable driver's seat and tilt steering



White / 800R

ENGINE

800R

Type	71 hp, Rotax® 799.9 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI)
Transmission	CVT, L / H / N / R / P, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok auto-locking front differential
Power Steering	N/A

SUSPENSIONS

Front Suspension	Double A-arm with sway bar / 10 in. (25.4 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Torsional Trailing arm Independent (TTI) with external sway bar 10 in. (25.4 cm) travel
Rear Shocks	Twin tube gas charged shocks

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

FEATURES

Gauge	Multifunction digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	N/A	Lighting	240 W from four 60-W projectors with tail lights / brake lights
Protection	N/A	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)

WARRANTY

Factory	6-months limited warranty
Extended	Up to 30 months B.E.S.T. coverage

TIRES / WHEELS

Front Tires	Maxxis Bighorn 2.0 27 x 9 x 12 in. (68.6 x 22.9 x 30.5 cm)
Rear Tires	Maxxis Bighorn 2.0 27 x 11 x 12 in. (68.6 x 27.9 x 30.5 cm)
Wheels	12-in. (30.5 cm) steel

DIMENSIONS / CAPACITIES

L x W x H	118.3 x 58.6 x 72 in. (300.4 x 148.9 x 182.9 cm)
Wheelbase	75.8 in. (192.4 cm)
Ground Clearance	11 in. (27.9 cm)
Dry Weight	1,291.4 lb (586 kg)
Rack Capacity	600 lb (272 kg) Dual-Level cargo box Upper level: 400 lb (181 kg) Lower level: 200 lb (91 kg)
Storage Capacity	Total: 8.3 gal (31.6 L) Glove box: 4.5 gal (17.2 L) Under driver seat: 3.5 gal (13.1 L) Center console: 0.3 gal (1.3 L)
Towing Capacity	1,500 lb (680 kg)
Fuel Capacity	10 gal (37.8 L)



©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved.™, ® and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. †Visco-Lok is a trademark of GKN ViscoDrive GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.

can-am.

Can-AmOffroad.com

