Section of the secti

CONFIDENT

•

•

1000R 100 hp, Rotax[®] 976 cc, V-twin, liquid cooled

Intelligent Throttle Control (iTC[™]) with Electronic Fuel Injection (EFI)

Quick Response System (QRS) CVT with high airflow ventilation and

Electronic Drive Belt Protection Extra-L / H / N / R / P Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential

> Electronic Hill Descent Control SPORT / ECO modes

> Dynamic Power Steering (DPS)

Double A-arm with sway bar / 12.5 in.travel

FOX 2.0 PODIUM Piggyback with QS3 compression adjustment

TTA with sway bar / 13 in. travel

FOX 2.0 PODIUM Piggyback with QS3 compression adjustment

Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers

Perfectly tuned

maintenance

Enhanced protection

More adventure and less

HIGHLIGHTS

PLATFORM FEATURES

- 60-in. wide
- 120.6-in. wheelbase
- Up to 13-in. suspension travel
 FOX† 2.0 PODIUM† QS3
- Piggyback shocks
- SPORT / ECO™ modes
 4 E in digital diaplay
- 4.5-in. digital displayPremium half doors
- Mudguards

DARING

- Sturdy engine and transmission
- Enhanced comfort and meaningful functionalities
- Can-Am design

ENGINES

Transmission

Drive Train Driving Assistance

Power Steering

Front Shocks

Rear Shocks

BRAKES Front

Rear

Rear Suspension

SUSPENSION Front Suspension


Fuel Delivery System

Туре

Dynamic Power Steering (DPS)
 Visco-Lok[‡] QE front differential

SPECIFIC TO DPS PACKAGE

Ergoprint seats with color accents
 Deinted color actions



Suspensions designed for

Ultra-resistant chassis

PRECISEEasy handling and

capabilities

performance



Can-Am Red / 10	OOR		
TIRES / WHEEL	S		
Front Tires	Maxxis† Bighorn 2.0† 27 x 9 x 12 in. (68.6 x 22.9 x 30.5 cm)		
Rear Tires	Maxxis Bighorn 2.0 27 x 11 x 12 in. (68.6 x 27.9 x 30.5 cm)		
Wheels	12-in. (30.5 cm) cast-aluminur		
DIMENSIONS /	CAPACITIES		
LxWxH	149 x 60 x 76.2 in (378.4 x 152.4 x 193.5 cm)		
Wheelbase	120.6 in. (306.3cm)		
Ground Clearance	12 in. (30.5 cm)		
Estimated Dry Weight	1,697 lb (769.7 kg)		
Chassis / Cage	Profiled cage ROPS approved		
Cargo Box Capacity	300 lb (136 kg)		
Storage Capacity	Total: 6.5 gal (24.7 L) Glove Box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and Cup holders 0.8 gal (3.1 L) Rear console and Cup holders: 1.2 gal (4.5L)		
Towing capacity	1,500 lb (680 kg)		
Fuel Capacity	10 gal (38 L)		

			ioning oupdoily	1,000 10 (000 16)	
			Fuel Capacity	10 gal (38 L)	
FEATURES					
Gauge 4.5 in. (11.4 cm) wide digital display: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, SPORT / ECO modes, seat belt, diagnostics, clock, battery voltage, engine temperature	Winch		N/A		
	meters, fuel, gear position, SPORT / ECO modes, seat belt, diagnostics, clock, battery voltage, engine	Steering Wheel Adjustable tilt steering		Adjustable tilt steering	
Instrumentation	Lighter type DC outlet in console (20-A)	Protection	Integrated from	Integrated front steel bumper, premium half doo	
Magneto	650-W	full skid plate, mudguards		ll skid plate, mudguards	
Lighting	TTwo 55 W reflectors and LED tail lights	Hitch Type		2-in hitch receiver	

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 30 months B.E.S.T. coverage

62/019 Bombardier Recreational Products Inc (BRP). All rights reserved. TM, [®] and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. ¹Visco-Lok is a trademark of GKN Viscodrive GmbH. ¹All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, teatures, models or equipment without incurring obligation. Some models depicted may include optional equipment, Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-noad use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years oid. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. * Vehicles featuring 30" ITP Cryptid tires are limited to 62 mph (100 km/h).

