## SMAVERICK X3 TURBO

## HIGHLIGHTS

## PLATFORM FEATURES

- 64-in. wide
- 102-in. wheelbase
- 14-in. of ground clearance
- High torque Dynamic Power Steering (DPS<sup>™</sup>)
- 20-in. suspension travel
- FOX† 2.5 PODIUM† QS3 Piggyback shocks
- 14-in. aluminum wheels
- 28-in. Maxxis† Bighorn 2.0† tires
- 4.5-in. digital display
- Rear tow hook
- DEFIANT

•

•

Rear

Extended

IT

Low seating position

way adjustable seats

Ergo-Lok cockpit with four-

- Trademark Can-Am DNA with next generation design + 120 hp turbocharged Rotax® ACE engine

POWERFUL

- PRECISE • TTX suspension with
  - industry leading travelUltra efficient and
- Advanced airflow dynamics
  QRS-X transmission
  Ultra efficient and lightweight chassis
  - Sharpest handling features
- ENGINETURBOType120 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc<br/>Turbocharged Triple-cylinder engine, liquid cooled and high-<br/>perfomance air filterFuel Delivery SystemIntelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)TransmissionQuick Response System X(QRS-X) CVT with high airflow,<br/>L / H / N / R / PDrive TrainSelectable 2WD / 4WD with Visco-Lok‡ auto-locking front differential<br/>High torque Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm with sway bar / 20-in. (50.8 cm) travel
Front Shocks	FOX 2.5 PODIUM Piggyback with QS3 compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar, 20-in (50.8 cm) travel
Rear Shocks	FOX 2.5 PODIUM Piggyback with QS3 compression adjustment and bottom-out control
BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers

Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers



Can-Am Red / TU White / TURBO Hyper Silver & Ca	JRBO an-Am Red / TURBO
<b>TIRES / WHEE</b>	LS
Front Tires	Maxxis Bighorn 2.0 28 x 9 x 14 in. 71.1 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 28 x 11 x 14 in. (71.1 x 27.9 x 35.6 cm)
Wheels	14-in. (35.6 cm) cast-aluminum

DIMENSIONS /	CAPACITIES	
LxWxH	132 x 64 x 65.4 in. (335.3 x 162.5 x 166.1 cm)	
Wheelbase	102 in. (259.1 cm)	
Ground Clearance	14 in. (35.6 cm)	
Estimated Dry Weight	1,481 lb (671.9 kg)	
Chassis / Cage	Dual-phase 980 steel	
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach	
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Center console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)	
Fuel Capacity	10.5 gal (40 L)	

Gauge	4.5 in. (11.4 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, SPORT / ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Protection	Integrated front bumper, quarter-doors, HMWPE full skid plate, rear tow hook
		Instrumentation	Lighter type DC outlet in central console
		Lighting	LED headlights and tail lights
Winch	N/A	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button
WARRANTY			

Up to 30 months B.E.S.T. coverage

©2019 Bombardier Recreational Products Inc (BRP). All rights reserved. <sup>TM</sup>, <sup>®</sup> and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. 'Visco-Lok is a trademark of GKN Viscodrive GmbH. 'All other trademarks are equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side wehice (SSY) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-oad expine. Were ride on paved surfaces or public roads. Operator us be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feed while seated against the backrest. Never engage in stunt driving and avoid concessive speed.





Can-AmOffroad.com