

# 2020 MAVERICK™ X3 X™ mr TURBO

## HIGHLIGHTS

### PLATFORM FEATURES

- 64-in. wide
- 102-in. wheelbase
- 14-in. of ground clearance
- High torque Dynamic Power Steering (DPS™)
- 18-in. suspension travel
- FOX† 2.5 PODIUM† QS3 Piggyback shocks
- 14-in. aluminum wheels

### SPECIFIC TO X mr PACKAGE

- Smart-Lok™\*\* front differential
- Snorkeled engine air intake and CVT
- 30-in. ITP†\* Cryptid† tires
- Front bumper, half-doors
- Front and rear tow hooks
- HMWPE full skid plate
- 4,500-lb (2,041kg) winch with synthetic rope
- X-package graphics/seats
- 7.6-in. digital display with keypad

### DEFIANT

- Trademark Can-Am DNA with next generation design
- Low seating position
- Ergo-Lok cockpit with four-way adjustable seats

### POWERFUL

- 120 hp turbocharged and intercooled Rotax® ACE engine
- Advanced airflow dynamics
- QRS-X transmission

### PRECISE

- TTX suspension with industry leading travel
- Ultra efficient and lightweight chassis
- Sharpest handling features

## ENGINE

## TURBO

Type	120 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT, high airflow with strategically positioned CVT air intakes and exhaust, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok™** technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD MUD / 4WD TRAIL <small>**Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry</small>
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS)

## SUSPENSIONS

Front Suspension	Double arched A-arm with sway bar / 18-in. (45.7 cm) travel
Front Shocks	FOX 2.5 PODIUM Piggyback with QS3 compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links / 18-in. (45.7 cm) travel
Rear Shocks	FOX 2.5 PODIUM Piggyback with QS3 compression adjustment and bottom-out control

## BRAKES

Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers

## FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, SPORT / ECO™ modes, seat belt, diagnostics, clock	Protection	Front bumper, half-doors, front and rear tow hooks, HMWPE full skid plate
Winch	4,500-lb (2,041 kg) winch with synthetic rope	Instrumentation	Lighter type DC Outlet in central console
		Lighting	LED headlights and tail lights with unique Can-Am LED signature
		Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button

## WARRANTY

Factory	6-months limited warranty
Extended	Up to 30 months B.E.S.T. coverage



■ Iron Gray & Manta Green / TURBO

## TIRES / WHEELS

Front Tires	ITP* Cryptid 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Rear Tires	ITP* Cryptid 30 x 11 x 14 in. (76.2 x 27.9 x 35.6 cm)
Wheels	14-in. (35.6 cm) cast-aluminum with machined finish

## DIMENSIONS / CAPACITIES

L x W x H	133 x 66.7 x 66.1 in. (337.8 x 169.4 x 167.9 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	14 in. (35.6 cm)
Estimated Dry Weight	1,664 lb (754.8 kg)
Chassis / Cage	Dual-phase 980 steel
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)

**BEST PROTECTION** ©2019 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. \* Vehicles featuring 30" ITP Cryptid tires are limited to 62 mph (100 km/h). \*Top Speed of 100 km/h (62 mph)

**can-am**



Can-AmOffroad.com