

HIGHLIGHTS

- · Rotax® V-Twin engine
- Intelligent Throttle Control (iTC™) with riding modes
- Front and rear FOX† 1.5 PODIUM† RC2 shocks
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- · Front, center and footwell aluminum skid plates
- A-arm and TTI HMWPE protectors
- 14 in. cast-aluminum beadlock wheels
- 26 in. ITP† Terracross† radial tires
- · Sport bumper with aluminum pre-runner
- Aluminum taper-profile handlebar with full-wrap handguards
- High-strength, multifunction racks with LinQ[™] quick-attach accessory system
- 625 W magneto
- 5.7 gal (21.4 L) water-resistant rear compartment
- X package coloration



Black, Hyper Silver & Can-Am Red / 1000R

ENGINE	1000R
Туре	91 hp, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI)
Transmission	CVT, P/R/N/H/L, standard engine braking
Drive Train	Selectable 2WD/4WD with Visco-Lok† QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel
Front Shocks	FOX 1.5 PODIUM RC2
Rear Suspension	Torsional Trailing-Arm Independent (TTI) 9.9 in. (25.1 cm) travel
Rear Shocks	FOX 1.5 PODIUM RC2
TIRES & WHEELS	
Front Tires	ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)
Rear Tires	ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)
Wheels	14 in. cast-aluminum beadlock
BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

DIMENSIONS & CAPACITIES

Estimated Dry Weight*	826 lb (375 kg)
LxWxH	86 x 48 x 49.5 in. (218.4 x 121.9 x 126 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	11 in. (27.9 cm)
Seat Height	34.5 in. (87.7 cm)
Rack Capacity	Front: 100 lb (45 kg)/Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,650 lb (750 kg)
Fuel Capacity	5.4 gal (20.5 L)

7.6 in. wide digital display: Speedometer, tachometer, odometer, trips and hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge, clock
Lighter type DC outlet in console, standard connector in the back (15 A)
RF Digitally Encoded Security System (D.E.S.S.™)
230 W from twin 60 W projectors and dual 55 W reflectors with tail light/brake light
Prewired for available winch
Standard
Front bumper with aluminum pre-runner Aluminum taper-profile handlebar with full-wrap handguards Front, center and footwell aluminum skid plates A-arm and TTI HMWPE protectors Mudguards

WARRANTY & EXTENDED SERVICE

EXTERNED CERTIFIC	
6-month BRP limited warranty	
B.E.S.T. term available up to 36 months	

