

HIGHLIGHTS

- Rotax[®] V-Twin engine options
- Arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with engine braking
- 12 in. cast-aluminum wheels
- 25 in. ITP[†] Holeshot ATR[†] tires
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Torsional Trailing-Arm Independent (TTI) rear suspension
- Visco-Lok[†] auto-locking front differential
- Multifunction digital gauge
- RF Digitally Encoded Security System (D.E.S.S.[™])



Desert Tan & Black / 570 / 850

ENGINES	570	850
Type	48 hp, Rotax 570 cc V-twin, liquid cooled	78 hp, Rotax 854 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)	Intelligent Throttle Control (ITC [™]) with Electronic Fuel Injection (EFI)
Transmission	CVT, P/R/N/H/L, standard engine braking	
Drive Train	Selectable 2WD/4WD with Visco-Lok auto-locking front differential	
Power Steering	N/A	

SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel	
Front Shocks	Oil	FOX [†] 1.5 PODIUM [†]
Rear Suspension	Torsional Trailing-Arm Independent (TTI) 9.9 in. (25.1 cm) travel	
Rear Shocks	Oil	FOX 1.5 PODIUM

TIRES & WHEELS

Front Tires	ITP Holeshot ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	ITP Holeshot ATR 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12 in. cast-aluminum

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

DIMENSIONS & CAPACITIES

	570	850
Estimated Dry Weight*	628 lb (286 kg)	681 lb (310 kg)
L x W x H	86 x 48 x 49 in. (218.4 x 121.9 x 124 cm)	
Wheelbase	51 in. (129.5 cm)	
Ground Clearance	10.5 in. (26.7 cm)	
Seat Height	34.5 in. (87.7 cm)	
Rack Capacity	Rear: 35 lb (16 kg)	
Storage Capacity	N/A	
Towing Capacity	1,300 lb (590 kg)	
Fuel Capacity	5.4 gal (20.5 L)	

FEATURES

Gauge	4.5 in. digital display: Speedometer, tachometer, odometer, trip and hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge and clock
Instrumentation	Lighter type DC outlet in console, standard connector in the back (15 A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.)
Lighting	240 W from 4 fender mounted projector beam headlamps (60 W) with tail light/brake light
Winch	Prewired for available winch
Seat	Standard
Protection	Front bumper

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 36 months