

can-am




MAVERICK TRAIL DPS 800 / 1000

2021

HIGHLIGHTS

AGILE	<ul style="list-style-type: none"> Sturdy engine and transmission Easy handling and capabilities Front and rear suspension designed for trail riding
ADVENTUROUS	<ul style="list-style-type: none"> Meaningful functionalities and versatility Enhanced comfort with Ergo-Lok cockpit Build the Maverick Trail that fits your needs
CONFIDENT	<ul style="list-style-type: none"> Can-Am design and proven fit and finish Enhanced protection More adventure and less maintenance
PLATFORM FEATURES	<ul style="list-style-type: none"> 50 in. wide 90.6 in. wheelbase 10 in. of ground clearance Up to 10.5 in. of suspension travel 4.5 in. digital display SPORT/ECO™ modes Half door (Only for 1000)
SPECIFIC TO DPS PACKAGE	<ul style="list-style-type: none"> Dynamic Power Steering (DPS™) Visco-Lok¹ QE front differential 12 in. (30.5 cm) aluminum wheels ErgoPrint seats with color accents



-  Triple Black / 800 / 1000
-  Octane Blue / 1000
-  Mossy Oak¹ Break-Up Country Camo¹ / 1000

ENGINES	800	1000
Type	51 hp, Rotax® 799.9 cc, V-twin, liquid cooled	75 hp, Rotax 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTCT™) with Electronic Fuel Injection (EFI)	
Transmission	Quick Response System (QRS) CVT with high-airflow ventilation and Electronic Drive Belt Protection Extra-L/H/N/R/P	
Drive Train	Selectable 2WD/4WD with Visco-Lok QE auto-locking front differential	
Driving Assistance	Electronic Hill Descent Control SPORT/ECO™ modes	
Power Steering	Dynamic Power Steering (DPS)	

SUSPENSIONS

Front Suspension	Double A-arm with sway bar/10 in. (25.4 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	TTA with sway bar/10.5 in. (26.7 cm) travel
Rear Shocks	Twin tube gas charged shocks

TIRES & WHEELS

Front Tires	Carlisle ¹ ACT ¹ 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle ACT 26 x 9 x 12 in. (66 x 22.9 x 30.5 cm)
Wheels	12 in. (30.5 cm) cast-aluminum

BRAKES

Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

	800	1000
Estimated Dry Weight	1,331 lb (603.7 kg)	1,364 lb (618.7 kg)
Chassis/Cage	Profiled cage, ROPS approved	
L x W x H	118 x 50 x 69 in. (300.5 x 127 x 175.3 cm)	
Wheelbase	90.6 in. (230.1 cm)	
Ground Clearance	10 in. (25.4 cm)	
Cargo Box Capacity	300 lb (136 kg)	
Towing Capacity	1,500 lb (680 kg)	
Storage Capacity	Total: 5.3 gal (20.2 L) Glove box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and cup holders: 0.8 gal (3.1 L)	
Fuel Capacity	10 gal (38 L)	

FEATURES

Gauge	4.5 in. (11.4 cm) wide digital display: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature	
Instrumentation	Lighter type DC outlet in console (20 A)	
Magneto	650 W	
Lighting	Two 55 W reflectors and LED tail lights	
Winch	N/A	
Steering Wheel	Adjustable tilt steering	
Protection	Integrated front steel bumper, Full skid plate	Integrated front steel bumper, Half doors, Full skid plate
Hitch Type	2 in. hitch receiver	

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months

© 2020 Bombardier Recreational Products Inc (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. ¹Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety, wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Ride responsibly.

