Can-am Maverick X3 MAX DS TURBO R

HIGHLIGHTS

Rear

пипсиптэ	
DEFIANT	Trademark Can-Am DNA with next generation design Low seating position Ergo-Lok cockpit with front and rear four-way adjustable seats
POWERFUL	 172 hp turbocharged and intercooled Rotax[®] ACE engine Advanced airflow dynamics QRS-X transmission
PRECISE	 TTX suspension with industry-leading travel Ultra efficient and lightweight chassis Sharpest handling features
PLATFORM FEATURES	 64 in. wide 135 in. wheelbase 14 in. of ground clearance High torque Dynamic Power Steering (DPS[™]) 20 in. suspension travel FOX† 2.5 PODIUM[↑] QS3 piggyback shocks 14 in. aluminum wheels 28 in. Maxxis[†] Bighorn 2.0[†] tires 4.5 in. digital display with keypad Rear tow hook
SPECIFIC TO DS TURBO R PACKAGE	• 172 hp Turbo R engine
ENGINE	TURBO R
Туре	172 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid cooled with integrated intercooler and high-perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high-airflow, L/H/N/R/P
Drive Train	Selectable 2WD/4WD with Visco-Lok [†] auto-locking front differential
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Double A-arm with sway bar/20 in. (50.8 cm) travel
Front Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar/20 in. (50.8 cm) travel
Rear Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment and bottom-out control
TIRES & WHEELS	
Front Tires	Maxxis Bighorn 2.0 28 x 9 x 14 in. (71.1 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 28 x 11 x 14 in. (71.1 x 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum
BRAKES	
Front	Dual 262 mm ventilated disc brakes
	with hydraulic twin-piston calipers



DIMENSIONS &

CAPACITIES	
Estimated Dry Weight	1,726 lb (782.9 kg)
Chassis/Cage	Dual-phase 980 steel
LxWxH	164 x 64 x 65.8 in. (416.6 x 162.5 x 167.1 cm)
Wheelbase	135 in. (342.9 cm)
Ground Clearance	13 in. (33 cm)
Rack Capacity	150 lb (68 kg) with LinQ™ quick-attach
Storage Capacity	Total: 3 gal (11.4 L) Glove box: 1.6 gal (6.2 L) Central console: 1.1 gal (4.1 L) Cup holders: 0.3 gal (1.1 L)
Fuel Capacity	10.5 gal (40 L)
FEATURES	
Gauge	4.5 in. (11.4 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Instrumentation	Lighter type DC outlet in central console
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights and tail lights
Winch	N/A
Protection	Integrated front bumper Quarter-doors HMWPE full skid plate Rear tow hook
WARRANTY & EXTENDED SERVICE	
Factory Warranty	6-month BRP limited warranty

 Extended Service Terms
 B.E.S.T. term available up to 30 months

© 2020 Bombardier Recreational Products Inc (BRP). All rights reserved. (®), TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. † Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety, wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Ride responsibly.

Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers

